

**BELGARD**  
PAVES THE WAY

**RESOURCE GUIDE |** AMCOR

## LIFETIME TRANSFERABLE LIMITED WARRANTY

Oldcastle® Architectural, Inc. ("Belgard") is proud to inform you that all of our interlocking concrete paver and retaining walls ("Products") meet and/or exceed the requirements of ASTM C-936 and ASTM C-1372. Belgard® guarantees its Products against these standards for the lifetime of the Product defined by ICPI. This guarantee does not apply to splitting, chipping or other breakage that could be caused by impact, abrasion or overloading. This warranty is transferable. The original proof of purchase is required.

This warranty is only valid if the material is installed under the guidelines of the ICPI ([www.ICPI.org](http://www.ICPI.org)), The NCMA ([www.NCMA.org](http://www.NCMA.org)) or the Belgard Installation Guideline Manual. Improper installation voids this warranty. This warranty is for residential applications only and does not apply to commercial applications. It is recommended that the job be installed by a Belgard Authorized Contractor who guarantees their workmanship for a minimum of 3 years from the date of install. For warranty service, contact Belgard at 1-877-BELGARD. A service representative will investigate your claim within 10 business days. If the Belgard product fails to meet the specifications, Belgard will replace the defective product at no charge. Color matching cannot be guaranteed. Belgard will not be responsible for any replacement labor, consequential damages or incidental damages. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE. SOME STATES DO NOT ALLOW FOR THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.

For specific information regarding warranty coverage and exclusions in regards to the Elements and Porcelain Paver products, please visit:  
**[Belgard.com/Warranty](http://Belgard.com/Warranty)**

# ABOUT US

At Belgard®, we take our role as industry leaders seriously. Our rigorous research and development program is centered on innovation and quality. We never take it for granted that our products are the best in the business and constantly strive to improve and take the industry to the next level. Our overarching goal is to continue to find new and exciting ways to create beautiful outdoor spaces while maintaining incredibly high standards for product quality and performance.

Since 1995, our locally made and nationally backed products have transformed thousands of residential and commercial properties across North America. With more shapes, styles and textures than any other brand, Belgard's Outdoor Living paving and wall products aren't just functional, they infuse outdoor spaces with distinctive atmosphere and style.

Every day, our network of Belgard Authorized Dealers and Contractors helps customers realize their outdoor dreams. And every year, we strive to improve our product and service offerings by dedicating more than 20,000 hours to research and development. By staying ahead of design trends, we are able to provide design-forward products that homeowners envision for their backyard spaces.

All of our outdoor products—when installed by a Belgard Authorized Contractor—are covered by a transferable lifetime limited warranty. That's just part of our commitment to lasting outdoor beauty.

# PAVERS & SLABS






## PRODUCTS

02	Cambridge Cobble®	18	Mega-Arbel® Patio Slab
04	Catalina Grana®	20	Mega-Bergerac®
05	Catalina™ Slate	22	Melville™ Plank
07	Dimensions™ 6	25	Origins™ 6
08	Dimensions™ 12	26	Origins™ 12
09	Dimensions™ 18	27	Origins™ 18
10	Dimensions™ Slabs & Borders	28	Origins™ Borders
13	Dublin Cobble® & Circle Kit	30	Plaza Paver
16	Holland Stone		

For basic paver installation information  
visit [icpi.org](http://icpi.org)




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓	✓*		

\*80mm Special Order only


## SHAPES & SIZES

**6 x 6**



6 x 6 x 2<sup>3</sup>/<sub>8</sub>  
6 x 6 x 3<sup>1</sup>/<sub>8</sub>\*

**6 x 9**



6 x 9 x 2<sup>3</sup>/<sub>8</sub>  
6 x 9 x 3<sup>1</sup>/<sub>8</sub>\*

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 60MM

6 X 6 X 2 <sup>3</sup> / <sub>8</sub>	120	12	10	480	48	.25	3145
6 X 9 X 2 <sup>3</sup> / <sub>8</sub>	112	11.2	10	300	30	.375	2995

### 80MM\*

6 X 6 X 3 <sup>1</sup> / <sub>8</sub>	96	12	8	384	48	.25	3156
6 X 9 X 3 <sup>1</sup> / <sub>8</sub>	90	11.25	8	240	30	.375	3197



## NOTES:


AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.






25% 6 x 6

75% 6 x 9






Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			✓

## SHAPES & SIZES


### 3-Piece Stone



6 x 12 x 2<sup>3</sup>/<sub>8</sub>



9 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 12 x 2<sup>3</sup>/<sub>8</sub>






UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE STONE

6 X 12 X 2 <sup>3</sup> / <sub>8</sub>	30	3	–	60	6	.5	–
9 X 12 X 2 <sup>3</sup> / <sub>8</sub>	30	3	–	40	4	.75	–
12 X 12 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	60	6	1	–
TOTAL	120	12	10	160	16	–	3280




Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			✓

## SHAPES & SIZES


### 3-Piece Stone



6 x 12 x 2<sup>3</sup>/<sub>8</sub>



9 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 12 x 2<sup>3</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE STONE


6 X 12 X 2 <sup>3</sup> / <sub>8</sub>	30	3	–	60	6	.5	–
9 X 12 X 2 <sup>3</sup> / <sub>8</sub>	30	3	–	40	4	.75	–
12 X 12 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	60	6	1	–
TOTAL	120	12	10	160	16	–	3322

## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.






Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.





Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			✓

## SHAPES & SIZES


### 3-Piece | 60mm



3 x 6 x 2<sup>3</sup>/<sub>8</sub>



6 x 6 x 2<sup>3</sup>/<sub>8</sub>



6 x 9 x 2<sup>3</sup>/<sub>8</sub>






UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

3 X 6 X 2 <sup>3</sup> / <sub>8</sub>	20	2	–	160	16	.125	–
6 X 6 X 2 <sup>3</sup> / <sub>8</sub>	40	4	–	160	16	.25	–
6 X 9 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	160	16	.375	–
TOTAL	120	12	10	480	48	–	3180




Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

## SHAPES & SIZES


### 3-Piece | 60mm



6 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 18 x 2<sup>3</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM






6 X 12 X 2 <sup>3</sup> / <sub>8</sub>	20	2	–	40	4	.5	–
12 X 12 X 2 <sup>3</sup> / <sub>8</sub>	40	4	–	40	4	1	–
12 X 18 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	40	4	1.5	–
TOTAL	120	12	10	120	12	–	3180

# DIMENSIONS™ 18

METROPOLITAN  
COLLECTION




Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

## SHAPES & SIZES


### 3-Piece | 60mm



9 x 18 x 2<sup>3</sup>/<sub>8</sub>



18 x 18 x 2<sup>3</sup>/<sub>8</sub>



18 x 27 x 2<sup>3</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

9 X 18 X 2 <sup>3</sup> / <sub>8</sub>	22.5	2.25	–	20	2	1.125	–
18 X 18 X 2 <sup>3</sup> / <sub>8</sub>	22.5	2.25	–	10	1	2.25	–
18 X 27 X 2 <sup>3</sup> / <sub>8</sub>	67.5	6.75	–	20	2	3.375	–
TOTAL	112.5	11.25	10	50	5	–	2925








# DIMENSIONS™ SLABS & BORDERS

METROPOLITAN  
COLLECTION 




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓*			✓

\*6 x 9 only


## SHAPES & SIZES

### 12 x 24 Slab | 60mm




12 x 24 x 2<sup>3</sup>/<sub>8</sub>

### 24 x 24 Slab | 60mm



24 x 24 x 2<sup>3</sup>/<sub>8</sub>

### 24 x 36 Slab | 60mm




24 x 36 x 2<sup>3</sup>/<sub>8</sub>

### 3 x 12 Border | 60mm



3 x 12 x 2<sup>3</sup>/<sub>8</sub>

### 6 x 9 Border | 60mm








6 x 9 x 2<sup>3</sup>/<sub>8</sub>

# DIMENSIONS™ SLABS & BORDERS

METROPOLITAN  
COLLECTION 



Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓*			✓

\*6 x 9 only

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
12 X 24 SLAB   60MM							
12 X 24 X 2 <sup>3</sup> / <sub>8</sub>	120	12	10	60	6	2	3230
24 X 24 SLAB   60MM							
24 X 24 X 2 <sup>3</sup> / <sub>8</sub>	80	8	10	20	2	4	2452
24 X 36 SLAB   60MM							
24 X 36 X 2 <sup>3</sup> / <sub>8</sub>	120	12	10	20	2	6	3230
3 X 12 BORDER   60MM							
3 X 12 X 2 <sup>3</sup> / <sub>8</sub>	110	11	10	440	48	.25	3014
6 X 9 BORDER   60MM							
6 X 9 X 2 <sup>3</sup> / <sub>8</sub>	112.5	11.25	10	300	30	.375	2982


## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

### 3-PIECE PATTERN A




21% - 3 x 6 | 23% - 6 x 6 | 56% - 6 x 9  
21% - 6 x 12 | 23% - 12 x 12 | 56% - 12 x 18

### 3-PIECE PATTERN B




21% - 3 x 6 | 23% - 6 x 6 | 56% - 6 x 9  
21% - 6 x 12 | 23% - 12 x 12 | 56% - 12 x 18

### 3-PIECE LARGE PATTERN A



21% - 9 x 18 | 23% - 18 x 18 | 56% - 18 x 27

### 3-PIECE LARGE PATTERN B








21% - 9 x 18 | 23% - 18 x 18 | 56% - 18 x 27

# DUBLIN COBBLE® & CIRCLE KIT

HERITAGE  
COLLECTION 



Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			

## SHAPES & SIZES

### 3-Piece | 60mm



$5\frac{15}{16} \times 2\frac{15}{16} \times 2\frac{3}{8}$



$5\frac{15}{16} \times 5\frac{15}{16} \times 2\frac{3}{8}$




$5\frac{15}{16} \times 8\frac{15}{16} \times 2\frac{3}{8}$

### Large Square | 60mm



$8\frac{15}{16} \times 8\frac{15}{16} \times 2\frac{3}{8}$

### Circle Kit | 60mm



Various x  $2\frac{3}{8}$

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

$5\frac{15}{16} \times 2\frac{15}{16} \times 2\frac{3}{8}$	19	1.9	–	160	16	.121	–
$5\frac{15}{16} \times 5\frac{15}{16} \times 2\frac{3}{8}$	38	3.8	–	160	16	.245	–
$5\frac{15}{16} \times 8\frac{15}{16} \times 2\frac{3}{8}$	57	5.7	–	160	16	.37	–
TOTAL	114	11.4	10	480	48	–	3150

### LARGE SQUARE | 60MM

$8\frac{15}{16} \times 8\frac{15}{16} \times 2\frac{3}{8}$	106	10.6	10	200	20	.55	3005
--	-----	------	----	-----	----	-----	------

### CIRCLE KIT | 60MM

VARIOUS X $2\frac{3}{8}$	75	7.5	10	–	–	–	2081
--------------------------	----	-----	----	---	---	---	------


## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

### 3-PIECE PATTERN A




17% - 3 x 6 | 33% - 6 x 6 | 50% - 6 x 9

### 3-PIECE PATTERN B



17% - 3 x 6 | 33% - 6 x 6 | 50% - 6 x 9

### 3-PIECE PATTERN C



17% - 3 x 6 | 33% - 6 x 6 | 50% - 6 x 9

### NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

### Installing circle pavers

- 1) Start by marking out circles on the surface to be paved.
- 2) Determine the dimensions of each concentric circle, as well as the layout details.
- 3) Always lay pavers starting from the center.
- 4) For a semicircle or quarter-circle, follow the same laying order.
- 5) Carefully follow the detailed instructions on installation guide.



To get a complete circle, be sure to follow the laying order illustrated at right.

Each pallet contains enough pavers for:

- 2 circles with a diameter of 6'5"
- or
- 1 circle with a diameter of 9'5"






2 pallets contains enough pavers for:

- 1 circle with a diameter of 13'6"





Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓	✓*		✓

\*80mm Special Order only


## SHAPES & SIZES

60mm



4 x 8 x 2<sup>3</sup>/<sub>8</sub>

80mm\*



4 x 8 x 3<sup>1</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
60MM							
4 X 8 X 2 <sup>3</sup> / <sub>8</sub>	120	12	10	540	54	.22	3144
80MM*							
4 X 8 X 3 <sup>1</sup> / <sub>8</sub>	96	12	8	432	54	.22	3355




## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

## 1-PIECE RUNNING BOND PATTERN




100% - 4 x 8

## 1-PIECE HERRINGBONE PATTERN



100% - 4 x 8

## 1-PIECE BASKET WEAVE PATTERN








100% - 4 x 8

# MEGA-ARBEL® PATIO SLAB

NATURAL  
COLLECTION



Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓*			

\*80mm Special Order only

## SHAPES & SIZES

60mm



15<sup>3</sup>/<sub>8</sub> x 21 x 2<sup>3</sup>/<sub>8</sub>

80mm\*



15<sup>3</sup>/<sub>8</sub> x 21 x 3<sup>1</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
60MM							
15 <sup>3</sup> / <sub>8</sub> X 21 X 2 <sup>3</sup> / <sub>8</sub>	104.4	8.7	12	72	6	2.24	2756
80MM*							
15 <sup>3</sup> / <sub>8</sub> X 21 X 3 <sup>1</sup> / <sub>8</sub>	78.3	8.7	9	54	6	2.24	2826




## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.






Percentages are based on area by paver.

100% 15<sup>3</sup>/<sub>8</sub> x 21





Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			

## SHAPES & SIZES

### 3-Piece | 80mm



$4\frac{3}{4} \times 9\frac{7}{16} \times 3\frac{1}{8}$




$9\frac{7}{16} \times 9\frac{7}{16} \times 3\frac{1}{8}$



$9\frac{7}{16} \times 14\frac{3}{16} \times 3\frac{1}{8}$

### Large Square | 80mm\*



$14\frac{3}{16} \times 14\frac{3}{16} \times 3\frac{1}{8}$

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
3-PIECE   80MM							
$4\frac{3}{4} \times 9\frac{7}{16} \times 3\frac{1}{8}$	12.4	1.55	–	40	5	.311	–
$9\frac{7}{16} \times 9\frac{7}{16} \times 3\frac{1}{8}$	29.76	3.72	–	48	6	.62	–
$9\frac{7}{16} \times 14\frac{3}{16} \times 3\frac{1}{8}$	44.64	5.5	–	48	6	.93	–
TOTAL	88	11	8	136	17	–	2957

### LARGE SQUARE | 80MM\*

$14\frac{3}{16} \times 14\frac{3}{16} \times 3\frac{1}{8}$	68	8.5	8	48	6	1.4	2504
--	----	-----	---	----	---	-----	------

\*Available Antiqued and Pre-Processed. Pre-Processed pallet weight is 2448.


## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

## 3-PIECE RUNNING BOND PATTERN



17% -  $4\frac{3}{4} \times 9\frac{7}{16}$  | 33% -  $9\frac{7}{16} \times 9\frac{7}{16}$  | 50% -  $9\frac{7}{16} \times 14\frac{3}{16}$






## 3-PIECE PATTERN



17% -  $4\frac{3}{4} \times 9\frac{7}{16}$  | 33% -  $9\frac{7}{16} \times 9\frac{7}{16}$  | 50% -  $9\frac{7}{16} \times 14\frac{3}{16}$



Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

SHAPES & SIZES

Small 3-Piece | 60mm



5 x 11<sup>13</sup>/<sub>16</sub> x 2<sup>3</sup>/<sub>8</sub>



5 x 15<sup>3</sup>/<sub>4</sub> x 2<sup>3</sup>/<sub>8</sub>



5 x 19<sup>11</sup>/<sub>16</sub> x 2<sup>3</sup>/<sub>8</sub>

Large 3-Piece | 60mm



7<sup>1</sup>/<sub>2</sub> x 11<sup>13</sup>/<sub>16</sub> x 2<sup>3</sup>/<sub>8</sub>








7<sup>1</sup>/<sub>2</sub> x 15<sup>3</sup>/<sub>4</sub> x 2<sup>3</sup>/<sub>8</sub>



7<sup>1</sup>/<sub>2</sub> x 19<sup>11</sup>/<sub>16</sub> x 2<sup>3</sup>/<sub>8</sub>



Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

## SMALL 3-PIECE | 60MM

5 X 11 <sup>13</sup> / <sub>16</sub> X 2 <sup>3</sup> / <sub>8</sub>	28.7	2.87	-	70	7	.41	-
5 X 15 <sup>3</sup> / <sub>4</sub> X 2 <sup>3</sup> / <sub>8</sub>	38.12	3.81	-	70	7	.55	-
5 X 19 <sup>11</sup> / <sub>16</sub> X 2 <sup>3</sup> / <sub>8</sub>	47.71	4.78	-	70	7	.68	-
TOTAL	114.53	11.45	10	210	21	-	3099

## LARGE 3-PIECE | 60MM

7 <sup>1</sup> / <sub>2</sub> X 11 <sup>13</sup> / <sub>16</sub> X 2 <sup>3</sup> / <sub>8</sub>	28	2.8	-	50	5	.62	-
7 <sup>1</sup> / <sub>2</sub> X 15 <sup>3</sup> / <sub>4</sub> X 2 <sup>3</sup> / <sub>8</sub>	38.15	3.82	-	50	5	.82	-
7 <sup>1</sup> / <sub>2</sub> X 19 <sup>11</sup> / <sub>16</sub> X 2 <sup>3</sup> / <sub>8</sub>	47.75	4.78	-	50	5	1.03	-
TOTAL	122.7	12.27	10	150	15	-	3259




## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

### 3-PIECE SMALL LINEAR PATTERN




25% - 5 x 11<sup>13</sup>/<sub>16</sub> | 33% - 5 x 15<sup>3</sup>/<sub>4</sub> | 42% - 5 x 19<sup>11</sup>/<sub>16</sub>

### 3-PIECE LARGE LINEAR PATTERN



25% - 7<sup>1</sup>/<sub>2</sub> x 11<sup>13</sup>/<sub>16</sub> | 33% - 7<sup>1</sup>/<sub>2</sub> x 15<sup>3</sup>/<sub>4</sub> | 42% - 7<sup>1</sup>/<sub>2</sub> x 19<sup>11</sup>/<sub>16</sub>






### 40% SMALL & 60% LARGE PATTERN



10% - 5 x 11<sup>13</sup>/<sub>16</sub> | 13% - 5 x 15<sup>3</sup>/<sub>4</sub> | 17% - 5 x 19<sup>11</sup>/<sub>16</sub>  
15% - 7<sup>1</sup>/<sub>2</sub> x 11<sup>13</sup>/<sub>16</sub> | 20% - 7<sup>1</sup>/<sub>2</sub> x 15<sup>3</sup>/<sub>4</sub> | 25% - 7<sup>1</sup>/<sub>2</sub> x 19<sup>11</sup>/<sub>16</sub>




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			✓

## SHAPES & SIZES


### 3-Piece | 60mm



3 x 6 x 2<sup>3</sup>/<sub>8</sub>



6 x 6 x 2<sup>3</sup>/<sub>8</sub>



6 x 9 x 2<sup>3</sup>/<sub>8</sub>






UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

3 X 6 X 2 <sup>3</sup> / <sub>8</sub>	20	2	–	160	16	.125	–
6 X 6 X 2 <sup>3</sup> / <sub>8</sub>	40	4	–	160	16	.25	–
6 X 9 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	160	16	.375	–
TOTAL	120	12	10	480	48	–	3312



Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

## SHAPES & SIZES


### 3-Piece | 60mm



6 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 12 x 2<sup>3</sup>/<sub>8</sub>



12 x 18 x 2<sup>3</sup>/<sub>8</sub>






UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

6 X 12 X 2 <sup>3</sup> / <sub>8</sub>	20	2	–	40	4	.5	–
12 X 12 X 2 <sup>3</sup> / <sub>8</sub>	40	4	–	40	4	1	–
12 X 18 X 2 <sup>3</sup> / <sub>8</sub>	60	6	–	40	4	1.5	–
TOTAL	120	12	10	120	12	–	3322




Scan for additional  
product information


PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

## SHAPES & SIZES


### 3-Piece | 60mm



9 x 18 x 2<sup>3</sup>/<sub>8</sub>



18 x 18 x 2<sup>3</sup>/<sub>8</sub>



18 x 27 x 2<sup>3</sup>/<sub>8</sub>






UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 60MM

9 X 18 X 2 <sup>3</sup> / <sub>8</sub>	22.5	2.25	–	20	2	1.125	–
18 X 18 X 2 <sup>3</sup> / <sub>8</sub>	22.5	2.25	–	10	1	2.25	–
18 X 27 X 2 <sup>3</sup> / <sub>8</sub>	67.5	6.75	–	20	2	3.375	–
TOTAL	112.5	11.25	10	50	–	–	3152




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓			✓

## SHAPES & SIZES

### 6 X 9 | 60mm



6 x 9 x 2<sup>3</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
6 X 9   60MM							
6 X 9 X 2 <sup>3</sup> / <sub>8</sub>	112.5	11.25	10	300	30	.375	2948




## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

### 3-PIECE PATTERN A




21% - 3 x 6 | 23% - 6 x 6 | 56% - 6 x 9  
21% - 6 x 12 | 23% - 12 x 12 | 56% - 12 x 18

### 3-PIECE PATTERN B




21% - 3 x 6 | 23% - 6 x 6 | 56% - 6 x 9  
21% - 6 x 12 | 23% - 12 x 12 | 56% - 12 x 18

### 3-PIECE LARGE PATTERN D



21% - 9 x 18 | 23% - 18 x 18 | 56% - 18 x 27

### 3-PIECE LARGE PATTERN E








21% - 9 x 18 | 23% - 18 x 18 | 56% - 18 x 27

# PLAZA PAVER

METROPOLITAN  
COLLECTION 




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓				✓

## SHAPES & SIZES

### Plaza | 50mm



23<sup>3</sup>/<sub>8</sub> x 23<sup>3</sup>/<sub>8</sub> x 2

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
PLAZA   50MM							
23 <sup>3</sup> / <sub>8</sub> X 23 <sup>3</sup> / <sub>8</sub> X 2	88	8	11	22	2	3.79	1958

# PERMEABLE PAVERS

## PERMEABLE PAVER INSTALLATION GUIDE

### 32 Basic PICP Systems

## PERMEABLE PAVERS

### 33 Aqua Dublin®

### 35 Aqualine™ 4½ x 9

### 37 Aqualine™ Ashlar



### 39 Turfstone™

For basic paver installation information  
visit [icpi.org](http://icpi.org)








# PERMEABLE INTERLOCKING CONCRETE PAVEMENT (PICP)

**PICP TYPICAL CROSS SECTION**





Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓		✓	✓

Permeable pavers are made to order.

## SHAPES & SIZES

### 3-Piece | 80mm



$2\frac{63}{64} \times 6\frac{13}{32} \times 3\frac{1}{8}$

$6\frac{15}{32} \times 6\frac{15}{32} \times 3\frac{1}{8}$

$6\frac{15}{32} \times 9\frac{13}{16} \times 3\frac{1}{8}$

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 80MM

$2\frac{63}{64} \times 6\frac{13}{16} \times 3\frac{1}{8}$	19.5	2.4	–	120	15	.162	–
$6\frac{15}{16} \times 6\frac{15}{16} \times 3\frac{1}{8}$	21.14	2.6	–	64	8	.324	–
$6\frac{15}{16} \times 9\frac{13}{16} \times 3\frac{1}{8}$	50.96	6.4	–	104	13	.4863	–
TOTAL	90.8	11.35	8	288	36	–	3100

## NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

17%  $2\frac{63}{64} \times 6\frac{13}{32}$

33%  $6\frac{15}{32} \times 6\frac{15}{32}$

50%  $6\frac{15}{32} \times 9\frac{13}{16}$








# AQUALINE™ 4½ X 9

ENVIRONMENTAL  
COLLECTION 




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓	✓	✓	✓

Permeable pavers are made to order.

## SHAPES & SIZES

80mm



4½ x 9 x 3⅞

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
80MM							
4½ X 9 X 3⅞	90	11.25	8	352	44	.281	3000

NOTE: Sold in herringbone machine lay pattern.  
Machine lay product will contain 1/2 pieces equating to 9 Sq.Ft. per pallet.



Mechanical  
Installation Only


**NOTES:**

AutoCAD® hatch pattern files can be downloaded from belgard.com for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.


Percentages are based on area by paver.

**1-PIECE BASKET WEAVE PATTERN**



100% - 4½ x 9






**1-PIECE HERRINGBONE PATTERN**



100% - 4½ x 9




Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓		✓	


Permeable pavers are made to order.

## SHAPES & SIZES


### 3-Piece | 80mm



4½ x 4½ x 3⅛




4½ x 9 x 3⅛



9 x 9 x 3⅛

### 4½ x 9 80mm



4½ x 9 x 3⅛

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	---------------	-------------------

### 3-PIECE | 80MM

4½ X 4½ X 3⅛	20.30	2.53	–	144	18	.141	–
4½ X 9 X 3⅛	47.21	5.901	–	168	21	.281	–
9 X 9 X 3⅛	22.48	2.81	–	40	5	.562	–
TOTAL	90	11.25	8	352	44	–	3000

### 4½ x 9 | 80MM

4½ X 9 X 3⅛	90	11.25	8	352	44	.281	3000
-------------	----	-------	---	-----	----	------	------

### NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.


Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

14%  $4\frac{1}{2} \times 4\frac{1}{2} \times 3\frac{1}{8}$






29%  $4\frac{1}{2} \times 9 \times 3\frac{1}{8}$

57%  $9 \times 9 \times 3\frac{1}{8}$





Scan for additional  
product information

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
				
✓	✓		✓	

Permeable pavers are made to order.

## SHAPES & SIZES

### 80mm



15<sup>3</sup>/<sub>4</sub> x 23<sup>5</sup>/<sub>8</sub> x 3<sup>1</sup>/<sub>8</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
80MM							
15 <sup>3</sup> / <sub>4</sub> X 23 <sup>5</sup> / <sub>8</sub> X 3 <sup>1</sup> / <sub>8</sub>	101	12.63	8	40	5	2.58	2424




### NOTES:

AutoCAD® hatch pattern files can be downloaded from [belgard.com](http://belgard.com) for use in architectural drawings.

Some patterns may not necessarily reflect the percentages of stone sizes within a particular pallet. In some cases you may have extras in one or more of the sizes. This must be accounted for in your planning and design.

Percentages are based on area by paver.

100% 15¾ x 23⅝



# PORCELAIN PAVERS & PLANKS

## PORCELAIN INSTALLATION GUIDE

- 42 Porcelain Paver Advantages
- 42 Specialty Tools for Porcelain Pavers Construction
- 43 Cleaning & Maintenance For Porcelain Products
- 43 Porcelain Paver Installation
- 44 Sand Set over Compacted Road Base Installation (Pedestrian Foot Traffic)
- 44 Sand Set over Concrete Overlay Installation (Pedestrian Foot Traffic)
- 45 Gravel Set over Open Graded Aggregate Installation
- 46 Cementitious Adhesive Overlay, Concrete Base Installation (Light Vehicular Traffic)

## PORCELAIN PAVERS & PLANKS

- |    |         |    |              |
|----|---------|----|--------------|
| 47 | Ardesie | 52 | Noon         |
| 48 | Glocal  | 53 | Quarziti 2.0 |
| 49 | Jurupa  | 54 | Silverlake   |
| 50 | Lagoon  | 55 | Verona™      |
| 51 | Na.Me   |    |              |

For basic paver installation information visit [icpi.org](http://icpi.org)  
Product availability varies by market. See Belgard Catalog for more information.

# PORCELAIN PAVERS

Belgard Porcelain Pavers are formed by pressing, followed by vitrification: this process involves the total fusion into a single material made from natural raw materials (sand, quartz, feldspars, kaolin, clays and inorganic pigments) which, fired at temperatures above 1226.67° C (2240° F), are transformed into a product with exceptional hardness, ultra-low absorption rate and unmatched mechanical characteristics. Belgard porcelain pavers are eco-compatible and ecolabel-certified. Each unit is 20mm (0.7874") standard thickness or ¾" nominal thickness and is durable enough to withstand use in exterior applications.

## PORCELAIN PAVERS ADVANTAGES:

- **Freeze thaw resistant**—They are 100% frost-free and their properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60° F to +140°F).
- **Color durability**—Color is fused by vitrification, becomes an integral part of the porcelain surface and is not affected by elements.
- **Easy installation**—Perfect fit and for fast installs.
- **Low absorption rate**—Spills, salt and other materials will not seep into pours.
- **Easy to clean**—Household cleaners can be used to wipe down spills and dirt; can even be pressure washed with a low pressure washing device\* (see pressure washing warning below).\*
- **Stylish**—Matches what homeowners are currently doing inside the home.
- **Durable**—High breakage loads of up to 3,587 lbs (1,627 kg) per foot based on ASTM-C648.
- **Resistant**— High compressive strength and ultra-low absorption rate creates a dense surface that resists mold, moss, dirt and other staining.
- **Skid-resistant**—Structured paver top textures create slip resistant surfaces for safety; perfect for around pools/spas or in wet climates.
- **Modular Design**—Superior accuracy in dimensional sizing and linear sides, the slabs allow for perfectly executed installations with tight and accurate lines.
- **Light weight**—16.8 kg (37 lbs) for the 24"x24" paver permit for easy installation, removal and serviceability and even reusability (Excluding adhered installations).
- Available in colors that have an SRI that qualifies for a LEED certification. The SRI on some units ranges between 60-80. To receive LEED credit, the SRI must be at least 29.
- **Impermeable**— Deicing salt and other deicing materials can be used without concern of damage.

\* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

## SPECIALTY TOOLS FOR PORCELAIN PAVER CONSTRUCTION:

- Wet cut tile saw equipped with a diamond blade manufactured for wet cutting porcelain.  
The saw should be designed to safely cut a 24 inch length porcelain paver.
- A paver clamp for easy handling, which can be used to both install and remove pavers.
- The use of gloves is highly recommended while handling and installing porcelain slabs.
- Appropriate notched trowels and grout float tools for cementitious adhesive and grout installation. The appropriate tool selection would be based on the adhesive and grout manufacturer's recommendation
- Pallets of porcelain pavers are manufactured and shipped with a Heavy Duty plastic protective pallet cover and the individual porcelain pavers are packaged in protective card board boxes. To prevent damage to your pavers, do not remove the protective card board boxes until you are ready to install them.
- Caution: Removing pavers from their protective packaging and handling multiple loose stones together creates the possibility for chipping.

Once the Heavy Duty plastic pallet covers have been removed from the pallet, the unused boxed pavers should be protected from the elements to insure the integrity of the protective cardboard boxes.

## CLEANING & MAINTENANCE FOR PORCELAIN PRODUCTS

Post-laying cleaning is obligatory after on site works. Inadequate or late removal of the grouting used on the joints can leave marks difficult to remove and create, on the flooring, a cement film able to absorb all types of dirt, thus giving the impression that it is the material that has become dirty.

It is indispensable to dissolve and remove these residues completely using buffered acids diluted in water (follow the instructions on the packs of the products used), which must then be removed completely and quickly, rinsing the floor with plenty of water to avoid residues or drops on the floor which could damage the tiles.

Allow the product to act on the wet floor, without letting it dry and rubbing it with colorless rags. Next, rinse it thoroughly with water to ensure that the floor is free of detergent residues. If necessary, repeat the operation.

We suggest performing a preliminary wash on a sample surface of a few square meters; if the test is successful, extend clearing over the entire surface. When you have done the above wash, carry out a basic or alkaline wash using degreasing detergents. This is because acid can leave grease on the floor, which could contribute to retaining dirt.


## PORCELAIN PAVER INSTALLATION

Each of the following option details will include specific information relative to the selected installation. Base thicknesses vary between different geographical and climatic locations and the contractor will be installing typical base thicknesses for paving installations in their location.


Installing porcelain pavers requires the bedding course sand to be pre-compacted and then struck off with a screed to the required thickness as shown in the detail drawings. The porcelain pavers are not compacted and therefore the sand layer beneath them requires pre-compaction. Do not compact dry sand, but insure the sand has a 5 to 6% moisture content so that it will compact cohesively and allow for a smooth strike off finish.

### INSTALLATION INFORMATION THAT MUST BE FOLLOWED :


- Weather, soil type and job conditions should be considered when choosing the best installation method.
- When installing porcelain planks (12 x 48, 8 x 48) always lay the pattern of the 1/3s. These should not be placed next to each other at 50%
- NEVER compact porcelain pavers with a plate compactor. Roller compactor recommended for all compaction with porcelain products
- ALWAYS pre-compact and strike off your sand leveling course before installing your porcelain pavers in sand set installations.
- A proper surface drainage system is required to mitigate standing water. Please consider that Belgard Porcelain Paves are impervious, therefore water must be properly discharged and drained away from the pavement.
- Porcelain pavers should only be wet cut with a tile saw equipped with a wet cut porcelain blade.
- NEVER install porcelain pavers without the required 4mm spacing between them. The porcelain pavers should never be installed with a porcelain to porcelain contact. Plastic 4mm spacers (shown at right) should be used on Sand Set and Permeable installations. The photo on the left illustrates the spacer installed in a perspective to support and space 4 paver corners and the photo on the right illustrates the installed spacer snapped apart (as designed) to form Space T that supports 2 paver corners. This versatility will permit your porcelain pavers to be installed in a stack bond pattern, a running bond patterns as well as a flush installation against another structure.
- For a 100 sf. project, approximately 34 spacers are needed; this allows for overages if needed.



4mm spacers




## SAND SET OVER COMPACTED ROAD BASE INSTALLATION (PEDESTRIAN FOOT TRAFFIC)



### INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method.
- Follow the detailed drawing above
- Base material is to be over based 6 to 8 inches beyond the edge of the pavement.
- Precompact the sand bedding course and screed to 1-in thickness with smooth surface
- The required edge restraint system is a low profile edge restraint with a vertical height of 1 1/2-in as shown in the drawing.
- Insure that pavement is constructed with a 1 1/2 to 2% slope that it is pitched away from any building.
- Insure the plastic 4mm spacers are installed at all corners of the installed pavers

## SAND SET OVER CONCRETE OVERLAY INSTALLATION (PEDESTRIAN FOOT TRAFFIC)




### INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method.
- A concrete curb with a full depth and finished height is needed to ensure full containment of the bedding sand and the Belgard Porcelain Pavers.
- Precompact the sand bedding course and screed to 1-in thickness with smooth surface
- Mechanically anchor edge restraint into the concrete base.
- Insure geotextile is installed directly on top of the concrete to contain the bedding sand.
- Insure that pavement is constructed with a 1 1/2 to 2 percent slope and that it is pitched away from any building.
- Insure the plastic 4mm spacers are installed at all corners of the installed pavers.

## GRAVEL SET OVER OPEN GRADED AGGREGATE INSTALLATION


PERIPHERAL RESTRAINT SYSTEM  
SPIKED INTO 6" TO 8" OVER BASE AREA



### INSTALLATION NOTES:

- Weather, soil type and job conditions should be considered when choosing the best installation method. Follow the detail drawing.
- The required edge restraint system for this installation has a vertical height of 2½ inches as shown in the drawing. Follow the edge restraint manufacturer's recommendations for the use of their product in permeable applications regarding geogrid usage and placement to maintain the performance of there edging.
- Ensure that pavement is constructed with a 2% slope and that it is pitched away from any building.
- Ensure the 4mm spacers are installed between all pavers.
- The open-graded aggregate should be clean and free from foreign matter, manufactured from crushed rock and conform to ASTM C33 size No. 57. Do not use recycled aggregates or rounded river gravel.
- Additional Drainage: If the project has fine-grained soils, silts or clays, and contributing water sources such as downspouts or groundwater, it is important to install a perforated pipe underdrain to prevent saturation of the subgrade. Make sure underdrain has an acceptable discharge location.
- When installing porcelain planks (12 x 48 & 8 x 48), always lay the pattern of 1/3's. These should not be placed next to each other at 50%.
- Roller Compactor recommended for all compaction with Porcelain products

## CEMENTITIOUS ADHESIVE OVERLAY, CONCRETE BASE INSTALLATION (LIGHT VEHICULAR TRAFFIC)




### INSTALLATION NOTES:

- Insure that pavement is constructed with a 2% slope and that it is pitched away from any building.
- For Cementitious adhesive and grout installation, refer to the manufacturer's technical instructions and specifically as they relate to outdoor installations.
- For concrete foundation slabs that are not large enough to require contraction / control joints, a minimum 4mm (1/8" to 3/16") grout joint is acceptable, but for larger concrete foundation slabs that do require contraction / control joints, the joint width should be a 3/8". It is absolutely imperative that all contraction / control joints be located in the joint line of installed porcelain pavers and not beneath a paver.
- Caution: If a Porcelain Paver is installed over a control joint, the paver will reflectively crack along the contraction / control joint beneath it.



Scan for additional  
product information




Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.


## SHAPES & SIZES

### 24 x 24\*



23.54 x 23.54 x 3/4

### Unico




12.99 x 23.54 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
24 X 24*							
23.54 X 23.54 X 3/4	232.5	2	7.75	30	–	3.85	2160
UNICO							
12.99 X 23.54 X 3/4	254.82	3	6.37	40	–	2.12	2080





Scan for additional  
product information




Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.  
\*\*Special Order

## SHAPES & SIZES

### 24 x 24\*



23.54 x 23.54 x 3/4

### 24 x 48




23.54 x 47.17 x 3/4

### 48 x 48\*\*



47.17 x 47.17 x 3/4

### Unico




12.99 x 23.54 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
<b>24 X 24*</b>							
23.54 X 23.54 X 3/4	232.5	2	7.75	30	—	3.85	2160
<b>24 X 48</b>							
23.54 X 47.17 X 3/4	271.25	1	7.75	35	—	7.71	2621
<b>48 X 48**</b>							
47.17 X 47.17 X 3/4	310	1	15.5	20	—	15.45	3009
<b>UNICO</b>							
12.99 X 23.54 X 3/4	254.82	3	6.37	40	—	2.12	2080



Scan for additional  
product information



Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓				✓

## SHAPES & SIZES

12 x 48




11.73 x 47.17 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
12 X 48							
11.73 X 47.17 X 3/4	271.25	2	7.75	35	—	3.84	2621



Scan for additional  
product information



Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓				✓

## SHAPES & SIZES

### 24 x 48




23.54 x 47.17 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
24 X 48							
23.54 X 47.17 X 3/4	271.25	1	7.75	35	—	7.71	2621



Scan for additional  
product information




Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.

## SHAPES & SIZES

### 24 x 24\*




23.54 x 23.54 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
24 X 24*							
23.54 X 23.54 X 3/4	232.5	2	7.75	30	—	3.85	2160



Scan for additional  
product information



Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓				✓

\*Special Order

## SHAPES & SIZES

### 12 x 48




11.73 x 47.17 x 3/4

### 8 x 48



7.64 x 47.17 x 3/4

### Unico



12.99 x 23.54 x 3/4

### Veneer\*




4.13 x 17.22

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
12 X 48							
11.73 X 47.17 X 3/4	279	2	7.75	36	—	3.84	2664
8 X 48							
7.64 X 47.17 X 3/4	151.8	2	5.06	30	—	2.5	1415
UNICO							
12.99 X 23.54 X 3/4	254.82	3	6.37	40	—	2.12	2080
VENEER*							
4.13 X 17.72	390.73	14	7.10	55	—	.51	1900



Scan for additional  
product information



Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.  
\*\*Special Order

## SHAPES & SIZES

### 12 x 24\*



11.73 x 23.54 x 3/4

### 24 x 24\*



23.54 x 23.54 x 3/4

### 24 x 48



23.54 x 47.17 x 3/4

### 24 x 36 | 12 x 24




23.54 x 35.35 x 3/4  
11.73 x 23.54 x 3/4

### 18 x 36



17.64 x 35.35 x 3/4

### Unico



12.99 x 23.54 x 3/4


### Veneer\*\*



4.13 x 17.22



Scan for additional  
product information



Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓


\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.

\*\*Special Order.

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
12 X 24*							
11.73 X 23.54 X 3/4	232.5	3	5.81	40	–	2.5	2201
24 X 24*							
23.54 X 23.54 X 3/4	232.5	2	7.75	30	–	3.85	2160
24 X 48							
23.54 X 47.17 X 3/4	271.25	1	7.75	35	–	7.71	2621
24 X 36   12 X 24							
23.54 X 35.35 X 3/4 11.73 X 23.54 X 3/4	279	1 PER SIZE	7.75	36	–	5.78 1.92	2640
18 X 36							
17.64 X 35.35 X 3/4	234.9	2	8.7	27	–	–	2235
UNICO							
12.99 X 23.54 X 3/4	254.82	3	6.37	40	–	2.12	2080
VENEER**							
4.13 X 17.72	390.7	14	7.10	55	–	.51	1900



Scan for additional  
product information




Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.

## SHAPES & SIZES

### 24 x 24\*



23.54 x 23.54 x 3/4

### 24 x 48




23.54 x 47.17 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
24 X 24*							
23.54 X 23.54 X 3/4	232.5	2	7.75	30	—	3.85	2160
24 X 48							
23.54 X 47.17 X 3/4	271.25	1	7.75	35	—	7.71	2621





Scan for additional  
product information




Spacers are recommended for all porcelain paver installations.  
PLEASE NOTE: For vehicular applications, must be a mortar install over a concrete slab.  
Please refer to the MIRAGE install guide for driveway install procedure.

PEDESTRIAN	LIGHT/REGULAR TRAFFIC	HEAVY TRAFFIC	PERMEABLE	ADA
✓	✓*			✓

\*Porcelain must be wet laid on concrete and concrete must be designed by an engineer to support the traffic load that will be imposed.


## SHAPES & SIZES

### 24 x 24\*



23.54 x 23.54 x 3/4

### Unico



12.99 x 23.54 x 3/4

UNIT	SQFT/ PALLET	PCS/ BOX	SQFT/ BOX	BOXES/ PALLET	UNITS/ LAYER	SQFT/ UNIT	WEIGHT/ PALLET
------	-----------------	-------------	--------------	------------------	-----------------	---------------	-------------------

### 24 X 24\*

23.54 X 23.54 X 3/4	232.5	2	7.75	30	—	3.85	2160
---------------------	-------	---	------	----	---	------	------

### UNICO

12.99 X 23.54 X 3/4	254.82	3	6.37	40	—	2.12	2080
---------------------	--------	---	------	----	---	------	------

# WALLS

## WALL INSTALLATION GUIDE

- 58 Wall Types
- 60 Before You Begin

## WALLS

- 61 Ashlar Tandem™
- 63 Belair Wall® 2.0
- 66 Diamond Pro® PS
- 68 Melville™ Wall
- 69 Melville Tandem™
- 71 Shelton Wall™ Tumbled
- 72 Steeple Crest™ Untumbled
- 73 Sterling®
- 74 Weston Stone™

For basic wall installation information  
visit [ncma.org](http://ncma.org)


# SEGMENTAL RETAINING WALL TYPES

Segmental retaining walls typically fall into one of three categories.

## GRAVITY RETAINING WALL

The first category — a gravity wall — is a retaining wall that does not use soil reinforcement. A gravity wall has height limitations specific to each product. An advantage of this type of retaining wall is that it requires a smaller work area behind the wall.


A gravity wall relies on the weight and setback of the block to resist the soil forces being exerted on the wall.



## GEOSYNTHETIC-REINFORCED RETAINING WALL

The second category is a geosynthetic-reinforced wall, which needs to be designed by a qualified engineer. There are (theoretically) no height limitations with reinforced retaining walls, and they are used in larger applications. It requires more work area behind the structure.

The block of soil is stabilized by introducing reinforcement layers into the soil mass behind the facing units. The larger the stabilized soil mass, the more soil can be retained or held back. The geogrid in the soil extends past the theoretical failure plane and serves to create a large, rectangular mass of block and soil, restraining the retained soil.




## ANCHORPLEX® SYSTEM

The third category is the Anchorplex system, which offers a unique, non-conventional solution to problematic wall construction sites. It is a retaining wall built with ANCHOR Diamond® products and structural backfill specified by ANCHOR Diamond, and backed by engineering support tools developed by Anchor.

Use of the Anchorplex system completely eliminates the need for the construction of a mechanically stabilized earth zone behind the wall facing and requires substantially less excavation than is usually necessary in geosynthetic-reinforced wall construction.

Contact ANCHOR Diamond at 1-877-295-5415 for more information about designing and building with the Anchorplex system.




## OTHER SEGMENTAL WALL APPLICATIONS

### INDEPENDENT TERRACED WALLS


For each wall to be independent of others, they must be built using a 2:1 ratio: The upper wall must be built a distance away from the lower wall of at least twice the height of the lower wall. In addition, the upper wall must also be equal to or less than the height of the lower wall. Exceptions to this general rule include weak soil conditions or where slopes exist above, below or between wall locations. For example, if the lower terrace is 4 feet tall, the distance between the terraces must be at least 8 feet and the upper wall must not be higher than 4 feet.

Proper drainage is vital to maintaining stable, long-lasting terraced walls. A drainpipe must be installed so that the water is directed around or under the lower wall. Never place the drainpipe outlet for the upper wall above or behind the lower wall.



### DEPENDENT TERRACED WALLS

When the distance between the lower and upper walls is less than twice the height of the lower wall, the walls become structurally dependent on each other. In this situation, it is important to take global stability into account, incorporating additional reinforcement — and longer layers — into the wall plan. In addition, structurally dependent walls require even more excavation, backfill and time. So plan ahead and be sure to check the wall plan for specific requirements. For structurally dependent walls, consult with a qualified engineer.



## BEFORE YOU BEGIN

Advance planning and careful layout at the job site help ensure a successful retaining and freestanding wall project.

- Review the site plan to confirm lot lines, wall location, length and elevations.
- Understand on-site soils. Ideal soils are sand and gravel. For walls built in clay or poor soils, work with a local engineer to confirm the wall design and the required soil reinforcement. Black or organic soils should not be used as backfill.
- Confirm the location of underground utilities. Call 811.
- Seek all necessary building permits.
- Prepare a drawing of the site with the wall location, lengths and elevations.
- Plan drainage to avoid erosion or buildup of water behind the wall. Consider where the water will drain through the wall, where downspouts will expel and whether there's an underground sprinkler. For walls greater than three feet in height, a perforated drainpipe is recommended at the base of the aggregate to quickly remove large amounts of water.
- A best practice is to divert water away from the wall before it has an opportunity to enter the reinforced soil and gravel fill zone.
- Check the block delivered to ensure it is the correct product and color. Check the geogrids to confirm that it's the strength and weight specified in the engineering plans.
- Be sure to use the right tools. Hand tools include a shovel, 4-foot level, dead-blow hammer, 2- or 3-pound hammer, chisel, hand tamper, hydraulic splitter and string line. Power tools may include a circular saw with a diamond blade and a plate compactor.
- Always wear protective eye wear.

For additional wall installation references go to [Belgard.com](http://Belgard.com).





Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓	✓	✓	✓	✓	✓	✓

## SHAPES & SIZES

Tandem Units	Tandem Cap	Modular Grid	Modular Block	Connector	U Start*
7 x 13 <sup>3</sup> / <sub>16</sub> x 2 <sup>5</sup> / <sub>8</sub> 7 x 15 <sup>13</sup> / <sub>16</sub> x 2 <sup>5</sup> / <sub>8</sub> 7 x 18 <sup>7</sup> / <sub>16</sub> x 2 <sup>5</sup> / <sub>8</sub>	15 x 24 x 3 <sup>1</sup> / <sub>4</sub>	8.31 sqft	7 <sup>1</sup> / <sub>16</sub> x 7 <sup>7</sup> / <sub>8</sub> x 7 <sup>7</sup> / <sub>8</sub>	50/Bag	18 <sup>7</sup> / <sub>16</sub> x 12 x 3 <sup>1</sup> / <sub>2</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	SQFT/ UNIT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	---------------	-----------------	-------------------

### TANDEM UNITS

7 X 13 <sup>3</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	19.2	3.2	–	30	.64	17	–
7 X 15 <sup>13</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	23.55	3.92	–	30	.77	21.5	–
7 X 18 <sup>7</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	27.35	4.56	–	30	.9	25	–
TOTAL	70.01	11.68	6	90	–	–	1954

### TANDEM CAP

15 X 24 X 3 <sup>1</sup> / <sub>4</sub>	17.33	2.17	8	32	2.5	96	3072
---	-------	------	---	----	-----	----	------

### MODULAR BLOCK

7 <sup>1</sup> / <sub>16</sub> X 7 <sup>7</sup> / <sub>8</sub> X 7 <sup>7</sup> / <sub>8</sub>	48.64	12.16	4	128	.36	20	2496
--	-------	-------	---	-----	-----	----	------

### U START BASE BLOCK\*

18 <sup>7</sup> / <sub>16</sub> X 12 X 3 <sup>1</sup> / <sub>2</sub>	86.05	12.29	7	56	–	54	3080
--	-------	-------	---	----	---	----	------

# ASHLAR TANDEM™ COLUMN

NATURAL  
COLLECTION



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓		✓		✓		

\*Recommended for use with all available wall block units. (Sold Separately) Note: U Start Base Block actual coverage length is 16<sup>11</sup>/<sub>16</sub>"


## SHAPES & SIZES

### Column Unit




7 x 18<sup>7</sup>/<sub>16</sub> x 2<sup>5</sup>/<sub>8</sub>

### Column Cap




3<sup>1</sup>/<sub>4</sub> x 24 x 24

### Column Grid




Height 42"

### 8" Connector



30/Bag

### U Start\*



18<sup>7</sup>/<sub>16</sub> x 12 x 3<sup>1</sup>/<sub>2</sub>

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

### ASHLAR VENEER COLUMN UNIT

7 X 18 <sup>7</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	54.52	9.09	6	60	1.12	25.53	1532
---	-------	------	---	----	------	-------	------

### TANDEM COLUMN CAP (SOLD SEPARATELY)

3 <sup>1</sup> / <sub>4</sub> X 24 X 24	–	–	8	16	–	149.25	2388
---	---	---	---	----	---	--------	------

### U START BASE BLOCK\*

18 <sup>7</sup> / <sub>16</sub> X 12 X 3 <sup>1</sup> / <sub>2</sub>	86.05 LNFT	12.29 LNFT	7	56	–	54	3080
--	---------------	---------------	---	----	---	----	------



Scan for additional  
product information


RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓	✓	✓	✓	✓		✓

## SHAPES & SIZES


### 6" Retaining Wall




6 x 6 x 8




6 x 10 x 8



6 x 16 x 8



6 x 16 x 8



3 x 7/8 x 13 1/2

### Corner/Column

### Cap

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

### 6" RETAINING WALL

6 X 6 X 8	3.75	1.25	–	15	4	19	–
6 X 10 X 8	6.25	2.08	–	15	2.4	34	–
6 X 16 X 8	20	6.67	–	30	1.5	51	–
TOTAL	30	10	3	60	–	–	2318

### CORNER/COLUMN

6 X 16 X 8	31.2	15.6	2	28	.64	65.5	1834
------------	------	------	---	----	-----	------	------

### CAP

3 X 7/8 X 13 1/2	90 LNFT	11.25 LFT	8	144	6.4	22.25	3204
------------------	---------	-----------	---	-----	-----	-------	------






# BELAIR WALL® 2.0 - LAYING PATTERN GUIDE

## USING A PATTERN FOR SINGLE-HEIGHT RETAINING WALLS

When using a pattern, begin at one edge, laying the units as indicated. Install at least one repeat of the pattern to establish the pattern before proceeding to the next course. Stagger the patterns as shown to avoid vertical bonds.

One set of 6-inch-high retaining wall blocks consists of 2 large units, 1 medium unit and 1 small unit, and is 2 square feet.


6" Multipiece wall system, 18-inch by 4-foot pattern = 6 sq. ft.



Blocks required		Blocks required	
6 Sets		3 Sets	
12	6" x 16"	6	6" x 16"
6	6" x 10"	3	6" x 10"
6	6" x 6"	3	6" x 6"


## WHEN TO USE A PATTERN FOR FREESTANDING WALLS


One set of 6-inch-high blocks consists of 2 large units, 1 medium unit and 1 small unit, and is 1 square foot of two sided wall.



**NOTE:** These freestanding wall installation patterns show only one side of the freestanding wall. The same number of blocks are needed to build the other side of a freestanding wall when using Belair Wall 2.0 and Brisa freestanding wall systems. Freestanding wall installation patterns are measured in length by height of one side of the wall, and are expressed in square feet. Sets of blocks required include the number of blocks needed to build both sides of the wall.

## TYPICAL CROSS SECTION






## TRAPEZOID DOUBLE-SIDED CAP

The double-sided cap has a right-angle side and an offset-angle side. The caps can be used in any of four directions since there is no specific top or bottom.

## STRAIGHT WALL


The cap must be laid alternately, narrow (N) and wide (W) faces, for a straight line. Always start capping from the lowest elevation.



## CURVES


Lay out the cap units side by side with same face facing out (wide faces for outside curves; narrow faces for inside curves). Occasional cutting of some pieces may be necessary.

Minimum radius: 7'6"




## 90-DEGREE CORNERS WITH CAP END

Using a Cap End unit




## FINISH WITH A CAP END

Do not cut the cap end, cut an interior cap if needed.



## STEPPING UP CAPS WITH CAP ENDS

If a wall elevation changes, caps can be stacked where the wall steps up. Begin laying caps at the lowest elevation and work your way toward the next step-up. Cut a cap unit directly on top of the capped portion of the wall with the cut side hidden from view. If not using a Cap End, place the trapezoid double-sided cap so that the side with the arrow is hidden.



**NOTE:** To split a block, use a hydraulic splitter or split manually by using a hammer and chisel to score the block on all sides. Pound the chisel on the same line until the block splits. If partial unit sides are not exposed, use a saw with a diamond blade to achieve a tighter fit.

# DIAMOND PRO® PS



Scan for additional  
product information

NATURAL  
COLLECTION  
METROPOLITAN  
COLLECTION  
LEGACY  
COLLECTION

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓	✓	✓	✓	✓		✓


## SHAPES & SIZES

### Smooth Face



8 x 18 x 12

### Straight Face



8 x 18 x 12

### Smooth Corner




8 x 17¼ x 7½

### Straight Corner




8 x 18 x 9

### Straight Cap




18 x 4 x 12

### Quarried Face



8 x 18 x 12

### Quarried Corner



8 x 17¼ x 7½

### ANCHOR Pins



5L x ½D



# DIAMOND PRO® PS



Scan for additional  
product information

NATURAL  
COLLECTION  
METROPOLITAN  
COLLECTION  
LEGACY  
COLLECTION

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓	✓	✓	✓	✓		✓

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

## SMOOTH FACE

8 X 18 X 12	32	8	4	32	1	65	2080
-------------	----	---	---	----	---	----	------

## SMOOTH CORNER

8 X 17¼ X 7½	36	18	2	24	2.13	75	1800
--------------	----	----	---	----	------	----	------

## STRAIGHT FACE

8 X 18 X 12	32	8	4	32	1	96	3060
-------------	----	---	---	----	---	----	------

## STRAIGHT CORNER

8 X 18 X 9	60	15	4	40	2.13	90	3600
------------	----	----	---	----	------	----	------

## STRAIGHT CAP

18 X 4 X 12	96 LNFT	12 LFT	8	64	.5	60	3840
-------------	---------	--------	---	----	----	----	------

## QUARRIED FACE

8 X 18 X 12	32	8	4	32	1	74	2368
-------------	----	---	---	----	---	----	------

## QUARRIED CORNER

8 X 17¼ X 7½	36	18	2	24	2.13	75	1800
--------------	----	----	---	----	------	----	------





## ANCHOR PIN SYSTEM

5L X ½D	—	—	—	100 / BOX	—	15 LBS / BOX	—
---------	---	---	---	-----------	---	--------------	---





Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING/ GARDEN WALL	RETAINING WALL
							
✓	✓	✓	✓	✓	✓	✓	


## SHAPES & SIZES

### Wall Unit



4 x 20 x 10

### Cap



2 x 20 x 13

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

### WALL UNIT

4 X 20 X 10	26.67	4.44	6	48	.56	64	3074
-------------	-------	------	---	----	-----	----	------









### CAP

2 X 20 X 13	120 LNFT	10 LFT	12	72	.28	42	3045
-------------	----------	--------	----	----	-----	----	------





Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
							
✓	✓	✓	✓	✓	✓	✓	✓


\*Recommended for use with all available wall block units. (Sold Separately) Note: U Start Base Block actual coverage length is 16<sup>11</sup>/<sub>16</sub>"

## SHAPES & SIZES

### Units 1, 2 & 3



7 x 13<sup>3</sup>/<sub>16</sub> x 2<sup>5</sup>/<sub>8</sub>




7 x 15<sup>13</sup>/<sub>16</sub> x 2<sup>5</sup>/<sub>8</sub>



7 x 18<sup>7</sup>/<sub>16</sub> x 2<sup>5</sup>/<sub>8</sub>

### Connector



7<sup>7</sup>/<sub>8</sub> x 6<sup>7</sup>/<sub>8</sub>  
(Connector not included)

### Modular Block




7<sup>1</sup>/<sub>16</sub> x 7<sup>7</sup>/<sub>8</sub> x 7<sup>7</sup>/<sub>8</sub>

### Connector



50 / Bag






### U Start\*



18<sup>7</sup>/<sub>16</sub> x 12 x 3<sup>1</sup>/<sub>2</sub>



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
							
✓	✓	✓	✓	✓	✓	✓	✓

\*Recommended for use with all available wall block units. (Sold Separately) Note: U Start Base Block actual coverage length is 16<sup>11</sup>/<sub>16</sub>"

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

## UNITS 1, 2 & 3

7 X 13 <sup>3</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	19.2	3.2	–	30	1.56	18.23	–
7 X 15 <sup>13</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	23.55	3.92	–	30	1.3	22.35	–
7 X 18 <sup>7</sup> / <sub>16</sub> X 2 <sup>5</sup> / <sub>8</sub>	27.35	4.56	–	30	1.12	26.04	–
TOTAL	70.1	11.68	6	90	–	–	1911

## TANDEM® MODULAR BLOCK

7 <sup>1</sup> / <sub>16</sub> X 7 <sup>7</sup> / <sub>8</sub> X 7 <sup>7</sup> / <sub>8</sub>	55.04	13.76	4	128	2.32	20	2496
--	-------	-------	---	-----	------	----	------

## U START BASE BLOCK®

18 <sup>7</sup> / <sub>16</sub> X 12 X 3 <sup>1</sup> / <sub>2</sub>	86.05 LNF	12.29 LNF	7	56	–	54	3080
--	-----------	-----------	---	----	---	----	------

# SHELTON WALL™ TUMBLED

HERITAGE  
COLLECTION **H**



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓	✓	✓	✓	✓	✓	✓	✓

\*Available Antiqued and Pre-Processed. \*\*Weight/Unit 513 Antiqued/540 PP and Weight/Pallet 2565 Antiqued/2700 PP

## SHAPES & SIZES

### Wall Units



6 x 6/4 x 10



6 x 12/10 x 10



6 x 16/14 x 10

### Cap



3 x 14/8 x 12

### Castlemanor Pins



6L x 3/8D

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	SQFT/ UNIT	WEIGHT/ LAYER	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	---------------	------------------	-------------------

### WALL UNITS

6 X 6/4 X 10	6.25	1.25	–	30	.208	–	–
6 X 12/10 X 10	13.75	2.75	–	30	.458	–	–
6 X 16/14 X 10	18.75	3.75	–	30	.625	–	–
TOTAL	38.75	7.75	6	90	–	813.8	4069

### CAP

3 X 14/8 X 12	49.5 LNFT	8.25 LNFT	6	54	4.36	32	1728
---------------	-----------	-----------	---	----	------	----	------

### CASTLEMANOR PIN SYSTEM

6L X 3/8D	–	–	–	80 / BAG	–	–	–
-----------	---	---	---	----------	---	---	---



# STEEPLE CREST™ UNTUMBLED

HERITAGE  
COLLECTION **H**



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓						✓	✓

## SHAPES & SIZES

### Wall Units



6 x 6/4 x 10




6 x 12/10 x 10



6 x 16/14 x 10

### Cap



3 x 14/8 x 12

### Castlemanor Pins



6L x 3/8D

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	SQFT/ UNIT	WEIGHT/ LAYER	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	---------------	------------------	-------------------

### WALL UNITS

6 X 6/4 X 10	2.62	.52	–	10	.25	–	–
6 X 12/10 X 10	5.5	1.1	–	10	.5	–	–
6 X 16/14 X 10	6.76	1.37	–	10	1.67	–	–
TOTAL	25.83	5.166	5	60	–	542.4	2712

### CAP

3 X 14/8 X 12	60 LNFT	10 LNFT	6	72	–	–	2039
---------------	---------	---------	---	----	---	---	------

### CASTLEMANOR PIN SYSTEM

6L X 3/8D	–	–	–	80 / BAG	–	–	–
-----------	---	---	---	----------	---	---	---



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
							
✓	✓	✓	✓*	✓*	✓*	✓*	✓

\*Can be split onsite to be a freestanding wall/corner application.


## SHAPES & SIZES

### SRW



6 x 17¾ x 12

### Cap



3 x 14/8 x 12

### AWS Pins











5L x ½D

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
SRW							
6 X 17¾ X 12	33.3	6.66	5	45	.74	78	3510
CAP							
3 X 14/8 X 12	49.5 LNFT	8.25 LNFT	6	54	.23	32	1728
AWS PIN SYSTEM							
5L X ½D	—	—	—	100 / BOX	—	15 LBS / BOX	—





Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITS	KITCHEN	FREESTANDING WALL	GARDEN WALL
							
✓	✓	✓	✓	✓	✓	✓	✓

## SHAPES & SIZES

### Universal



4 x 12 x 8

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
UNIVERSAL							
4 X 12 X 8	42	6	7	126	0.33	29	3696

# WESTON STONE™ INSTALLATION INSTRUCTIONS







This is a pinless system. Maximum wall height is 2½ feet. Walls exceeding 2½ feet in height may require geogrid reinforcing and the consultation of a qualified engineer. Contact your Belgard sales representative or dealer for assistance.

Weston Stone wall units must be glued with a quality construction adhesive to develop the necessary mechanical bond. All measurements herein are approximate. Natural materials are used in the manufacturing of this product.

## WESTON STONE™ WALL PATTERNS

### TYPICAL CROSS SECTION WITH WESTON STONE SEAT WALL

### TREE RINGS WITH WESTON STONE



# NOTES



# FIRE FEATURES

## FIRE FEATURES INSTALLATION GUIDE

78 Installation Instructions

## FIRE FEATURES

- 79 Bordeaux™ Series
- 82 Brighton™ Series
- 84 Bristol™ Series
- 88 Country Fire Pit
- 89 Weston Stone™ Fire Pit

# STANDARD INSTALLATION INSTRUCTIONS

## GRAVEL BASE

Gravel Fill shall be a clean angular stone or angular granular fill meeting the following gradation as determined in accordance with ASTM D 422.

<u>Sieve Size</u>	<u>Percent Passing</u>
1-in	100
3/4-in	75-100
No. 4	0-60
No. 40	0-50
No. 200	0-12

## FOUNDATION PREPARATION

Following excavation of the leveling pad, foundation soil shall be examined to assure the actual foundation soil strength meets or exceeds the assumed design bearing strength. Soils not meeting the required strength shall be removed and replaced with soil meeting the design criteria.



*Scan for Fortified Installation Method  
to be used with soft soils or expanding clays*

## LEVELING PAD PREPARATION

A minimum 18-in thick layer or compacted granular material shall be placed for use as a leveling pad up to the grades and locations as shown on the construction drawings. The granular base shall be compacted to a firm, level bearing pad on which to place the bottom level of the unit. A leveling pad consisting of 6-in (minimum) thick lean, unreinforced concrete may be used at the contractor's option, or if so detailed on the plans. The leveling pad should extend a minimum of 6-in from the toe and from the heel of the unit base.

## GRAVEL FILL

Gravel fill shall be placed to the minimum finished thickness and width shown on the construction plans.

Gravel lifts shall be a maximum thickness of 6-in.

Lifts shall be compacted by three passes of a light weight vibratory plate compactor.


For areas not affected by freeze-thaw conditions please contact your local Belgard sales representative for further installation information.

# BORDEAUX™ SERIES

NATURAL  
COLLECTION




Scan for additional  
product information







# BORDEAUX™ SERIES



## FIREPLACE

Rough Dimensions:  
2' 7" D x 4' 3" W x 7' 8" H


Approximate Weight:  
4200 lbs.



## WOOD BOXES

Rough Dimensions:  
2' 1" D x 3' 5" W x 3' 1" H


Approximate Weight:  
3070 lbs.



## GRILL ISLAND

Rough Dimensions:  
2' 8" D x 6' W x 3' 5" H

Approximate Weight:  
2500 lbs.




# BORDEAUX™ SERIES

## LINEAR FIRE TABLE

Rough Dimensions:  
2'10<sup>3</sup>/<sub>4</sub>" D x 6'2" W x 2'4<sup>3</sup>/<sub>4</sub>" H


Approximate Weight:  
2500 lbs.



## LINEAR FIREPLACE

Rough Dimensions:  
2'6"D x 7'1"W x 5'4"H

Approximate Weight:  
3700 lbs.



### FIREPLACE

70300791

Bordeaux Wood Fireplace  
Colors: Lamina Sienna/Cordova  
Stone Buff Base + Top

13070014

Bordeaux Wood Fireplace  
Colors: Lamina Sienna/Cordova  
Midnight Base + Top

### WOOD BOXES

13140001

Bordeaux Wood Boxes (Pair)  
Colors: Lamina Sienna/  
Cordova Stone Buff

13140020

Bordeaux Wood Boxes (Pair)  
Colors: Lamina Sienna/  
Cordova Stone Midnight

*36" wood burning fireplace can be  
converted to a vented gas unit on-site.*

### GRILL ISLAND

13110010

Bordeaux Grill Island (NG)  
Colors: Lamina Sienna/  
Cordova Stone Buff  
+ Stainless

13110011

Bordeaux Grill Island (LP)  
Colors: Lamina Sienna/  
Cordova Stone Buff  
+ Stainless

13110014

Bordeaux Grill Island (NG)  
Colors: Lamina Sienna/  
Cordova Stone Midnight  
+ Stainless

13110015

Bordeaux Grill Island (LP)  
Colors: Lamina Sienna/  
Cordova Stone Midnight  
+ Stainless

### LINEAR FIREPLACE

13000021

Bordeaux Linear Fireplace  
Colors: Sienna/Buff

13000019

Bordeaux Linear Fireplace  
Colors: Sienna/Midnight

13000020

Bordeaux Linear Fireplace  
Colors: Pewter/Midnight

### LINEAR FIRE TABLE

13000023

Bordeaux Linear Fire Table  
Colors: Sienna/Buff

13000204

Bordeaux Linear Fire Table  
Colors: Sienna/Midnight

13000203


Bordeaux Linear Fire Table  
Colors: Pewter/Midnight

# BRIGHTON™ SERIES

HERITAGE  
COLLECTION **H-I**



*Scan for additional  
product information*



# BRIGHTON™ SERIES

## FIREPLACE

Rough Dimensions:  
3'4"D x 4'4"W x 8'4"H

Approximate Weight:  
5825 lbs.

### FIREPLACE

70580007

Brighton Fireplace


Colors: Weston Gascony Tan/Urbana  
Ashbury Haze Base + Top

70580378

Brighton Fireplace

Colors: Weston Cotswold Mist/Urbana  
Brookstone Slate Base + Top

36" wood burning fireplace can be  
converted to a vented gas unit on-site.



## WOOD BOXES

Rough Dimensions:  
2'4"D x 3'W x 2'11"H

Approximate Weight:  
3200 lbs.

### WOOD BOXES

70300046



Brighton Wood Boxes (Pair)

Colors: Weston Gascony Tan/Urbana  
Ashbury Haze

70580291

Brighton Wood Boxes (Pair)

Colors: Weston Cotswold Mist/Urbana  
Brookstone Slate



# BRISTOL™ SERIES

NATURAL  
COLLECTION



Scan for additional  
product information



# BRISTOL™ SERIES

## FIREPLACE

Rough Dimensions:  
3'D x 5'W x 9'6"H

Approximate Weight:  
5825 lbs.

## FIREPLACE


70580261

Colors: Weston Gascony Tan/  
Arbel Ashbury Haze Base + Top

70580312

Colors: Weston Cotswold Mist/  
Arbel Brookstone Slate Base + Top

36" wood burning fireplace can be  
converted to a vented gas unit on-site.



## WOOD BOXES

Rough Dimensions:  
2'4"D x 3'W x 3'3"H

Approximate Weight:  
3950 lbs.


## WOOD BOXES (PAIR)

70580334

Colors: Weston Gascony Tan/  
Urbana Ashbury Haze

70580534

Colors: Weston Cotswold  
Mist/Urbana  
Brookstone Slate



## HEARTH

Rough Dimensions:  
2'D x 5'W x 11"H

Approximate Weight:  
1180 lbs.



## ARCHED HEARTH

70580262


Colors: Weston Gascony Tan/  
Arbel Ashbury Haze

70580309

Colors: Weston Cotswold Mist/  
Arbel Brookstone Slate



# BRISTOL™ SERIES



## GRILL ISLAND

Rough Dimensions:  
3'D x 6'8"W x 4'4"H

Approximate Weight:  
3980 lbs.

## GRILL ISLAND

13110008




Bristol Grill Island (NG)

Colors: Weston Gascony Tan/  
Arbel Ashbury Haze + Stainless

11130250

Bristol Grill Island (LP)

Colors: Weston Gascony Tan/  
Arbel Ashbury Haze + Stainless



## FIRE PIT KITS INSTALLATION INSTRUCTIONS

- Always use in accordance with all applicable local and state fire codes
- Failure to follow these instructions could result in a hazardous fire causing property damage or physical injury
- Caution: For outdoor use only
- Use the fire ring on stone, dirt or sand surfaces
- For adult use only — do not allow children to use the fire ring
- Do not use on lawns, wooden decks, concrete or asphalt
- Do not use fire ring indoors or under a patio roof
- Do not use in windy conditions
- Do not leave fire unattended at any time
- Do not use under tree branches, trellis, or overhangs of any kind, including covered porches
- Do not use flammable liquids such as gasoline, alcohol, diesel fuel, kerosene, or charcoal lighter fluid to light or relight fires as this may also cause paint to flake off fire ring
- Care should be taken to make sure all combustible material is far enough away from the fire ring not to ignite it
- Avoid using softwoods such as pine or cedar because they are likely to throw sparks — hardwoods are recommended
- Keep children and pets away from the fire ring while it is in use
- Exercise the same precautions you would with any open fire
- Do not wear flammable or loose clothing when tending an open fire
- Avoid touching surfaces as they will be extremely hot
- Assure the fire is completely extinguished before leaving fire ring
- Any modifications to this appliance may be dangerous and are not permitted

### ADDITIONAL MATERIALS NEEDED

- Tamper
- Level
- 2 Bags of Leveling Sand
- 2 Tubes of Concrete Adhesive
- Caulk Gun
- 3 Bags of Gravel or Lava Rock
- Shovel
- Optional Marking Paint or Chalk



# COUNTRY FIRE PIT

HERITAGE  
COLLECTION **H-I**



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PIT	KITCHEN	FREESTANDING WALL	RETAINING WALL
✓				✓			


## SHAPES & SIZES

### Fire Pit Unit



4 x (8<sup>3</sup>/<sub>4</sub>/6) x 7<sup>3</sup>/<sub>8</sub>

### Cap Unit



3 x 14/8 x 12

### Metal Ring\*



\*Sold seperately.

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	----------------	-----------------	-------------------

### FIRE PIT UNIT

4 X (8 <sup>3</sup> / <sub>4</sub> /6) X 7 <sup>3</sup> / <sub>8</sub>	—	—	4	68	17	14	950
--	---	---	---	----	----	----	-----

### CAP UNIT









3 X 14/8 X 12	49.5 LNFT	8.25 LNFT	6	54	9	32	1728
---------------	-----------	-----------	---	----	---	----	------

# WESTON STONE™ FIRE PIT

HERITAGE  
COLLECTION 




Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	COLUMNS	FIRE PITs	KITCHEN	FREESTANDING WALL	RETAINING WALL
							
✓				✓			

Completed kit utilizing 12 per course, 4 courses high yields: 28" Inside, 44" Outside, 16" Tall. Not available in 2023


## SHAPES & SIZES

### Universal




4 x 12 x 8

### Metal Insert\*



\*Sold separately.

### Metal Insert\*



\*Sold separately.

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ SQFT	WEIGHT/ UNIT	WEIGHT/ PALLET
UNIVERSAL							
4 X 12 X 8	—	—	3	48	—	19.79	950

# NOTES









# ACCESSORIES

## ACCESSORIES

- 92 Artforms™
- 93 Anglia Edger®
- 95 Landings™ Step Unit
- 98 Marina™ Coping
- 100 Melville™ Coping



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	CAPS	FIRE PITS	KITCHEN	FREESTANDING WALL	RETAINING WALL
							
✓			✓	✓	✓		

## SHAPES & SIZES


### 18 x 36\*

### Installation




18 x 36 x 3


\*Pallets contain both  
open and closed  
ended units




Anchor  
Slide & Nut  
50 per box




Joining  
Plate  
10 per box



Outer  
Corner  
10 per box



Inner  
Corner  
10 per box



Stretcher  
10 per box

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	UNITS/ SQFT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	----------------	-------------------


## ARTFORMS

18 X 36 X 3	81	9	9	18*	2	4.5	2562**
-------------	----	---	---	-----	---	-----	--------

\*Total number of both open and closed end panels. 18 x 36 pallets contain 9 of each.






\*\*150 lbs is the weight for the closed units, 148 lbs is the weight for the open units.

### 18 X 36 X 3






Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	CAPS	COPING
				
✓				

## SHAPES & SIZES


### Edger Units




5 1/4 x 8 x 8 1/8



5 1/4 x 8 x 10 1/2



5 1/4 x 8 x 15 5/8







5 1/4 x 8 x 18

UNIT	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ PALLET	UNITS/ LAYER	UNITS/ SQFT	WEIGHT/ PALLET
------	-----------------	----------------	------------------	------------------	-----------------	----------------	-------------------

### EDGER UNIT

5 1/4 X 8 X 8 1/8	7.9	4	-	12	1.52	24.29	-
5 1/4 X 8 X 10 1/2	10.23	4	-	12	1.14	35.33	-
5 1/4 X 8 X 15 5/8	15.23	4	-	12	.768	48.58	-
5 1/4 X 8 X 18	35.39	8	-	24	.67	56.31	-
TOTAL	68.75	20	3	60	20	-	2482

# ANGLIA EDGER INSTALLATION INSTRUCTIONS



# LANDINGS™ STEP UNIT

NATURAL  
COLLECTION



Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	CAPS	COPING
✓	✓	✓		

## SHAPES & SIZES

### Step Unit



6 x 48 x 18

UNIT	LNFT/ PALLET	UNITS/ PALLET	LAYER/ PALLET	UNITS/ LAYER	UNITS/ LNFT	WEIGHT/ UNIT	WEIGHT/ PALLET
STEP UNIT							
6 X 48 X 18	24	6	3	2	.25	421	2526






# LANDINGS™ STEP UNIT INSTALLATION

Each Landings™ Step Unit is manufactured with two unique face patterns. The step units are palletized and packaged for easy skid-steer loader removal. Care needs to be taken in handling these units. If a blemish occurs on one side of unit, rotate 180° before setting unit into place.


## BASE COURSE

Excavate an area 6 inches deep by 1 foot longer by 1 foot wider than the installed step(s) size. Add a minimum of 6 inches of compactable base material, 3/4-inch minus (with fines) aggregate. Compact and level. Set unit and, if desired, add a slight pitch of no more than 1/4 inch toward the front of the step to shed moisture. If installing step units next to a retaining wall, keep units level from front to back.

The Textures on Sides 1 and 2 are Designed to Nest with Minimal Gapping Between the Units.



Place Units so They Nest Tightly Together.



Two unique faces on each step

## STAIR TREAD


For each consecutive step, follow base course instructions, making sure the top of the base is even with the top of the previously installed unit. Recommended tread depth is a minimum of 10 inches, but no more than 16 inches. When installing steps adjacent to a finished surface such as pavers, as illustrated, a 6-inch-tall dummy block needs to be installed below the first step.

## LANDING

For landing(s) follow base course instructions. Each step unit is manufactured with two unique face patterns. The face patterns are manufactured to nest together, which will create a narrower joint, providing pleasing aesthetics.

## STEPS IN A 90-DEGREE WALL

When building into a retaining wall, construct the steps first and build the walls adjacent to the steps.





## SKID-STEER LOADER

Slide forks underneath the first step unit and lift off pallet. Set the step unit onto its desired location, using a spacer to ease in fork removal.



A helpful tip to protect the step unit is to wrap the fork of the skid-steer with corrugated plastic packaging from the pallet or other protective materials. Secure to the forks.



## CLAMP

Using a materials clamp, center the clamp on the step unit. Attach clamp to skid-steer or mini-excavator and slowly lift the step unit off of the pallet and move it into place. Be sure to have a second person to help guide the unit into place as the machine sets the step unit down.



## STRAPS

When using a heavy duty strap(s), start by wrapping the strap(s) around the center if using one or close to step unit ends if two straps are being used. Cinch the strap(s) tight and attach the looped ends of the strap(s) to skid-steer or mini-excavator. Slowly lift the step unit from the pallet and move it into place. Be sure to have a second person to help guide the unit into place as the machine sets the step unit down. Using a spacer will help to ease in the strap removal.








## CART

When using a cart, place provided corrugated plastic from pallet or other protective material onto the cart to help protect the step unit. With help from a second person, slowly slide the step unit from the pallet onto the cart. Maneuver the unit carefully into place.

Videos can be found on our YouTube channel:  
[www.youtube.com/anchorblockmn](http://www.youtube.com/anchorblockmn)




Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	CAPS	COPING
				
✓	✓	✓	✓	✓

## SHAPES & SIZES


### Coping Unit



6 x 12 x 2<sup>3</sup>/<sub>8</sub>

UNIT	LNFT/ PALLET	UNITS/ PALLET	LAYER/ PALLET	UNITS/ LAYER	UNITS/ LNFT	WEIGHT/ UNIT	WEIGHT/ PALLET
COPING UNIT							
6 X 12 X 2 <sup>3</sup> / <sub>8</sub>	63	126	3	42	2	13.6	1711

# MARINA COPING - POOL INSTALLATION




# MARINA COPING - STEP INSTALLATION

## OPTION 1

- A. Marina Coping
- B. Wall Block
- C. Grey block (4 in x 8 in x 16 in) or Wall Block


Note: All elements must be glued together with the concrete adhesive



## OPTION 2






- A. Marina Coping
- B. Wall Block

Note: A & B elements must be glued together with the concrete adhesive.






Scan for additional  
product information

RESIDENTIAL	COMMERCIAL	STEPS	CAPS	COPING
				
✓		✓	✓	✓

## SHAPES & SIZES

### Coping Unit



15<sup>3</sup>/<sub>4</sub> x 23<sup>5</sup>/<sub>8</sub> x 3<sup>9</sup>/<sub>16</sub>

UNIT	LNFT/ PALLET	UNITS/ PALLET	LAYER/ PALLET	UNITS/ LAYER	UNITS/ LNFT	WEIGHT/ UNIT	WEIGHT/ PALLET
COPING UNIT							
15 <sup>3</sup> / <sub>4</sub> X 23 <sup>5</sup> / <sub>8</sub> X 3 <sup>9</sup> / <sub>16</sub>	55.125	28	7	4	1.97	101.5	2842



**BELGARD®** | PAVES  
THE WAY™

**AMCOR LOCATIONS**

333 S. Redwood Road  
North Salt Lake, UT 84054  
Ph: 800-800-4004

1820 E / CO-402,  
Loveland, CO 80537

**STAY CONNECTED WITH BELGARD.**



[Pinterest.com/Belgard](https://www.pinterest.com/Belgard)



[Facebook.com/OutdoorLivingbyBelgard](https://www.facebook.com/OutdoorLivingbyBelgard)



[Belgard.com/Blog](https://www.belgard.com/blog)



[YouTube.com/BelgardHardscapes](https://www.youtube.com/BelgardHardscapes)



[Twitter.com/Belgard](https://twitter.com/Belgard)



[Instagram.com/BelgardOutdoorLiving](https://www.instagram.com/BelgardOutdoorLiving)