





Beauty, functionality and quality are hallmarks of the Belgard Commercial Aqualine permeable pavers. The innovative design features of the permeable paver systems are hallmarks of the Aqualine Ashlar 3-Piece permeable paver. The innovative design features of this permeable paver system make a perfect pavement choice for machine or hand-installed driveways, plazas, parking lots and alleyways.

Benefits of Aqualine[™] Ashlar 3-Piece:

Belgard's Aqualine permeable pavement systems can eliminate stormwater runoff and improve water quality

- Interlocking spacer bars for increased structural performance
- Smooth surface texture with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Meet the requirements of ASTM C936

Benefits by the numbers:


Chamfer Width: 3 mm

Spacer Bar Width: 10 mm

Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)

• Surface Open Area: 12%

Pallet Layer:



Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

Aqualine™ Ashlar 3-Piece

Approximate Dimensions

Pavers

4½"x4½"

4½"x9"

9"x9"

Available Thickness: 31/8" (80 mm)









Hardscapes Sales & Resource Center 625 Griffith Rd., Suite 115 Charlotte, NC 28317 800-545-5080

Belgard.com/Blog

Get Social

