

PLACE ADDITIONAL PANEL AT CORNER TO PROVIDE 100% GEOGRID COVERAGE OF REINFORCED FILL. THIS PANEL SHOULD BE PLACED ONE COURSE ABOVE MAIN REINFORCEMENT.

TRIM OVERLAPPED PANELS AT BACK OF BLOCK FACE TO REDUCE OVERLAP. WHERE AREAS OF OVERLAP OCCUR, PLACE AT LEAST 2 INCHES OF REINFORCED FILL BETWEEN GRID LAYERS.

USE A MASONRY SAW TO ACHIEVE DESIRED ANGLES. CUT UNITS TO MAINTAIN RUNNING BOND.

NOTE:
FREE-DRAINING AGGREGATE (NOT SHOWN) TO SPAN 10 FT. ALONG THE WALL FACE AND TO THE BACK OF THE REINFORCED ZONE

PANEL 2

PANEL 1

COURSE A

GEOGRID REINFORCEMENT

COURSE B



© 2018 Anchor Wall Engineering, LLC
© and ™ Anchor Wall Systems, Inc.
www.anchorwall.com

This drawing is for illustrative purposes only and should not be used for construction without the signature of a registered professional engineer.

Brookshire™ Wall System

Inside Angles

Scale:

1/2" = 1'-0"

Drawn by:

SB

Date:

9/14/2018

Drawing number:

BR0906RE32