





DESIGNFORMS™




**2.5FT VERTICAL PLANTER
- CONCRETE TOP**




COMPONENTS



Large Panel (x16)
12" x 24"




Small Panel (x8)
6" x 24"




Hardware Kit (x5)


REQUIRED TOOLS




LEVEL



MEASURING TAPE




CARPENTER SQUARE




DRILL



**DEEP HEX SOCKET
7/16" WITH 1/4" DRIVE**



**SOCKET ADAPTOR
1/4" HEX SHANK TO 1/4" DRIVE**




RUBBER Mallet


SAFETY EQUIPMENT



SAFETY BOOTS



GLOVES




SAFETY GLASSES

BASE PREPARATION

ALWAYS LEVEL GROUND BEFORE INSTALLATION


ON NEW OR EXISTING PATIO



SLAB OR PAVER




BEDDING SAND 1"




COMPACTED AGGREGATES 6" - 8"




SOIL



ON POURED CONCRETE




REINFORCED POURED CONCRETE FOUNDATION 2"




COMPACTED AGGREGATES 6" - 8"



SOIL



ON COMPACTED FOUNDATION




SLAB OR PAVER



COMPACTED AGGREGATES 6" - 8"



SOIL





TIPS & TRICKS

READ ALL INSTRUCTIONS BEFORE ASSEMBLY

PREBUILD:

- Prebuild all hardware prior to starting build.
- When assembling hardware SNAP the bolt into place with the plastic sliders. Pressing down on something flat and hard will help. (Fig. A)
- Do not over hand tighten the slider/bolt piece and the nut on the completed brackets. They should be loosely attached so they slide into the channels on the panels. Leave a space of ¼ in. (Fig. B)




Fig. A

INSTALL:

- Always start in the corner when starting a build. (Fig. C)
- Set the drill clutch (torque) at a low level to deliver a torque range of 50-65lbs per inch. Refer to your drill manual for torque adjustment instructions.
- Use a rubber mallet to assist with moving/aligning/adjusting panel placement during assembly.




Fig. B

WHEN BUILDING WOODEN COMPONENTS:

- Do not exceed prescribed length. Exact measurements are required for proper assembly.
- Ensure your cuts are straight.
- Do not over tighten the screws into the wood - this can cause buckling.
- Pre-drill holes for 45° corner assemblies.
- Use cedar or pressure treated wood for outdoor use.
- Seal wooden components for prolonged use.




Fig. C

WHEN BUILDING PLANTERS:

- Line the inside of the planters or garden beds with a geotextile fabric to help with water management.






DESIGNFORMS™

2.5FT VERTICAL PLANTER - CONCRETE TOP





BRACKET A

x8






BRACKET B

x4




BRACKET C

x22



BRACKET H




x12



ASSEMBLY I

x46

Use with
BRACKETS B and H
during build




J

x46






1




2






3




4






5




6






7




$d1 = d2$






8




9






10




11






12




13






14




15






16







17






18



USE MIDDLE I SLIDER
FOR STEP 18







DESIGNFORMS™

2.5FT VERTICAL PLANTER - CONCRETE TOP


19

x 3







20






21

x 3







22





23






DESIGNFORMS™



2.5FT VERTICAL PLANTER - CONCRETE TOP

24






25






26







27






28






29






30





31





32

