# NORR STONE FINISH | 20MM



The stone-like look of pebbles in various colors and shapes creates a threedimensional effect that adds a natural yet contemporary touch to any surface.










RR 02 ST - STA



v2 SVART RR 03 ST - STA



v. FARGE RR 05 STA



**v3** HAV RR 06 STA



v4 OKEN RR 08 STA



GRUS **RR 09 STA** 







ν4 LOW SOLAR HEAT HIGH VARIATION ABSORPTION

## PALLET INFORMATION

v3

MODERATE

VARIATION

NORR		SQFT/ Pallet	SQFT/ Box	BOXES/ PALLET	PCS/ BOX	WEIGHT/ BOX	WEIGHT/ PALLET
24 X 24	23.54 x 23.54 x <sup>3</sup> ⁄4	232.5	7.75	30	2	72	2160
32 X 32	31.42 x 31.42 x <sup>3</sup> ⁄4	289.33	6.89	42	1	65.48	2751

Downloadable professional resources available at Belgard.com/Resources

#### **QUALITY FOR LIFE**


Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty** 

### FEATURES & BENEFITS

- · Features pebbles of varying colors and shapes to create a pleasant three-dimensional effect
- Incredibly high breakage loads, up to 3,000 pounds
- Modular for faster installation
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.\*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials
- · Structured top textures create non-slip surfaces
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F)

\* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

## SHAPES & SIZES



View the product page on Belgard.com for more information



ТАМРА 4630 Woodland Corporate Blvd. Tampa, FL 33614 Ph: 813-783-1970

AN OLDCASTLE<sup>®</sup> APG OUTDOOR BRAND

BELGARD<sup>®</sup> | PAVES THE WAY