

# STERLING<sup>®</sup>

## WALL SYSTEM

A VERSATILE RETAINING OR FREESTANDING WALL SYSTEM THAT  
INSTALLS WITH AN EASY TO LOCATE PIN SYSTEM





# STERLING®

## WALL SYSTEM

A VERSATILE RETAINING OR FREESTANDING WALL SYSTEM THAT INSTALLS WITH AN EASY TO LOCATE PIN SYSTEM

### ☑ FEATURES & BENEFITS

- Build retaining walls with easy pin alignment and side view for placement visualization
- Block channels make easy pin alignment for battered or freestanding retaining walls
- Score marks for splitting block to make a two-sided freestanding wall unit
- Center score mark provides guide for splitting to make corner or column units
- Hand holds allow for easier handling during installation
- Maximum gravity retaining wall height is 4 ft\*
- Retaining wall minimum inside radius, measured on the base course to the front of the units: 6 ft
- Retaining wall minimum outside radius, measured on the top course to the front of the units: 4 ft
- Maximum freestanding wall (FSW) height is 3 ft\*
- Freestanding wall minimum radius 4 ft
- Maximum column height is 4 ft\*
- Segmental retaining wall setback/system batter 10.6°

### 📦 SHAPES & SIZES

#### FREESTANDING WALL BLOCK



6 x 17¾ x 10

#### RETAINING WALL BLOCK



6 x 17¾ x 12

#### ANCHOR™ FIBERGLASS PINS\*



5 x ½

#### UNIVERSAL CAP



3 x 18/12 x 13

\* Not included on pallet.

### 🔴 AVAILABLE COLORS



TOSCANA



VICTORIAN

**BELGARD®** PAVES THE WAY

For more info, visit [Belgard.com](http://Belgard.com)

**AMCOR**  
333 S. Redwood Road  
North Salt Lake, UT 84054  
Ph: 1-800-800-4004

1820 E / CO-402,  
Loveland, CO 80537  
Ph: 970-669-0535



© 2022 Oldcastle® APG, Inc. A CRH Company. All Rights Reserved.  
Revised: 12/08/22 BEL22-412\_Amcors