

BELAIR WALL[®] 2.0

FREESTANDING & RETAINING WALL

CHISELED STONE APPEARANCE FOR SOPHISTICATED LANDSCAPES



BELGARD
PAVES THE WAY[™]



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS





BELAIR WALL® 2.0

FREESTANDING & RETAINING WALL

CHISELED STONE APPEARANCE FOR SOPHISTICATED LANDSCAPES

☑ FEATURES & BENEFITS

- Freestanding & gravity walls* can be built up to 3 feet high, including buried course
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Rear-lip on retaining wall block makes installation fast and accurate
- Freestanding Walls: 4-foot minimum radius using all 3 units
- Retaining Walls: 1"/9.5° Setback/System batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 8 feet

🧱 SHAPES & SIZES**

SRW



6 x 6 x 8



6 x 10 x 8



6 x 16 x 8

FSW



6 x 6 x 5



6 x 10 x 5



6 x 16 x 5

COLUMN/CORNER



6 x 16 x 8

TRAPEZOID DOUBLE-SIDED CAP



3 x 7/8 x 13 1/2

CAP END 3-SIDED



3 x 8 x 13 1/2

WALL END 3-SIDED



6 x 8 x 11

U START BASE BLOCK®



3 1/2 x 18 1/2 x 12

🔥 AVAILABLE COLORS



COLOR

BELGARD® | PAVES THE WAY

For more info, visit Belgard.com

SUPERLITE
1919 W Fairmont Dr., Ste. 5
Tempe, AZ 85282
Ph: 1-800-366-7877



© 2023 Oldcastle® APG, Inc. A CRH Company. All Rights Reserved.
Revised: 04/26/23 BEL22-412_Superlite