

BELAIR WALL[®] 2.0

FREESTANDING & RETAINING WALL

CHISELED STONE APPEARANCE FOR SOPHISTICATED LANDSCAPES



BELGARD
PAVES THE WAY[™]



BACKED BY
ANCHOR
DIAMOND
INDUSTRY EXPERTS





BELAIR WALL® 2.0

FREESTANDING & RETAINING WALL

CHISELED STONE APPEARANCE FOR SOPHISTICATED LANDSCAPES

☑ FEATURES & BENEFITS

- Freestanding & gravity walls* can be built up to 3 feet high, including buried course
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Rear-lip on retaining wall block makes installation fast and accurate
- Freestanding Walls: 4-foot minimum radius using all 3 units
- Retaining Walls: 1"/9.5° Setback/ System batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 8 feet

📦 SHAPES & SIZES**

SRW



6 x 6 x 8



6 x 10 x 8



6 x 16 x 8

FSW



6 x 6 x 5



6 x 10 x 5



6 x 16 x 5

COLUMN/CORNER



6 x 16 x 8

TRAPEZOID DOUBLE-SIDED CAP



3 x 7/8 x 13½

CAP END 3-SIDED



3 x 8 x 13½

WALL END 3-SIDED



6 x 8 x 11

U START BASE BLOCK®



3½ x 18½ x 12

🔥 AVAILABLE COLORS



DARK CHARCOAL



RIO



TOSCANA



VICTORIAN

BELGARD® | PAVES THE WAY

For more info, visit Belgard.com

CPM
4110 192nd St. East
Tacoma, WA 98446
Ph: 844-371-5138



© 2022 Oldcastle® APG, Inc. A CRH Company. All Rights Reserved.
Revised: 12/07/22 BEL22-412_CPM