

ECO DUBLIN[®]

PERMEABLE PAVER

THE CLASSIC LOOK OF CUT STONE IN A MULTI-PIECE COMBINED WITH PERMEABLE TECHNOLOGY TO REDUCE STORMWATER RUNOFF





ECO DUBLIN[®]

PERMEABLE PAVER

THE CLASSIC LOOK OF CUT STONE IN A MULTI-PIECE COMBINED WITH PERMEABLE TECHNOLOGY TO REDUCE STORMWATER RUNOFF

☑ FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Optimal joint openings for infiltration
- Can be mechanically or manually installed
- Can be utilized to construct an ADA-compliant pavement
- Joint Width: 12 mm
- Initial Surface Infiltration Rate: >500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 7%
- Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

🔹 AVAILABLE COLORS



DANVILLE BEIGE






LUEDERS GRAY

Swatch represents product color only, not surface texture, dimension and/or shape.

📦 SHAPES & SIZES

3-PIECE MODULAR | 80MM

-  3½ x 6⅞ x 3⅞
-  6⅞ x 6⅞ x 3⅞
-  10¼ x 6⅞ x 3⅞

BELGARD[®] | PAVES THE WAY

For more info, visit Belgard.com

JEWELL
1607 Spur 529
Rosenburg, TX 77471
Ph: 281-342-8114

400 Jewell Drive
Waco, TX 76712
Ph: 254-772-3440



© 2022 Oldcastle[®] APG, Inc. A CRH Company. All Rights Reserved.
Revised: 06/27/23 BEL22-412_Jewell