# BELAIR WALL®

# RETAINING | FREESTANDING



A sophisticated appearance of hand-chiseled stone is brought to life with an irregular surface that adds depth and visual interest for a dynamic look.









HICKORY NEWPORT GRAY

SILEX BLEND















## PALLET INFORMATION

BELAIR WALL°		SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ Pallet	WEIGHT/ Pallet
6" FSW	6 x 8 / 6 x 11	18	-	-	36	1580
	6 x 16 / 14 x 11					
6" SRW	6 x 8 x 8	30	-	-	60	2360
	6 x 16 x 8					
	6 x 16 x 8 w/ micro joint					
CORNER	6 x 16 x 8	-	-	-	20	1200
CAP	3 x 7 / 8 x 13½	-	-	-	144	3260
CAP END	3 x 8 x 13½	-	-	-	36	882
WALL	6 x 8 x 11		-	-	42	1550

Downloadable professional resources available at **Belgard.com/Resources** 


#### **QUALITY FOR LIFE**

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty** 

### FEATURES & BENEFITS

- · Elegant chiseled-stone face
- Freestanding & gravity walls\* can be built up to 3 feet high, including buried course
- Taller walls can be built using geosynthetic reinforcement when designed by a qualified engineer
- Rear-lip on retaining wall block makes installation fast and accurate
- Freestanding Walls: 4-foot minimum radius using all 3 units
- Retaining Walls: 1"/9.5° Setback/ System batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 8 feet

## SHAPES & SIZES



View the product page on **Belgard.com** for more information

