


PORCELAIN COLLECTION

# GLOCAL

CONCRETE FINISH | 20MM



The smooth concrete-like finish offers a clean, contemporary aesthetic. Its structured and tight surface texture in neutral shades makes this porcelain paver a versatile design element.



**v2** CLEAR  
GC 01



**v2** PERFECT\*  
GC 02



**v2** IDEAL  
GC 03




**v2** TYPE  
GC 04



**v2** CLASSIC  
GC 05



**v2** ABSOLUTE\*  
GC 06



**v2** CHAMOIS\*  
GC 08

\*Special order

Due to the natural materials in our products, colors may vary from those shown on the cut sheet. We recommend viewing actual product samples to ensure the perfect color and finish for each project.



SLIGHT  
VARIATION



LOW SOLAR HEAT  
ABSORPTION

## QUALITY FOR LIFE

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at [Beldgard.com/Warranty](https://Belgard.com/Warranty)

## FEATURES & BENEFITS

- Elegant smooth face and texture
- Incredibly high breakage loads, up to 3,000 pounds
- Modular for faster installation,
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.\*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials.
- Structured top textures create non-slip surfaces.
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F).

*\* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.*

## SHAPES & SIZES

24 X 24



23.54 x 23.54 x 3/4

24 X 48



23.54 x 47.17 x 3/4

48 X 48



47.17 x 47.17 x 3/4

## PALLET INFORMATION

	GLOCAL	SQFT/ PALLET	SQFT/ BOX	BOXES/ PALLET	PCS/ BOX	WEIGHT/ BOX	WEIGHT/ PALLET
24 X 24	23.54 x 23.54 x 3/4	232.5	7.75	30	2	72	2160
24 X 48	23.54 x 47.17 x 3/4	271.25	7.75	35	1	74	2621
48 X 48	47.17 x 47.17 x 3/4	310	15.5	20	1	148.5	3009

Downloadable professional resources available at [Beldgard.com/Resources](https://Beldgard.com/Resources)

View the product page  
on [Beldgard.com](https://Beldgard.com) for  
more information



LEARN MORE

**BELGARD®** | PAVES  
THE WAY™

AN OLDCASTLE® APG OUTDOOR BRAND

**OLDCASTLE SOLUTIONS CENTER**  
1919 W Fairmont Dr. Suite 5  
Tempe, AZ 85282  
Ph: 800-366-7877

© 2025 Oldcastle® APG, Inc. All Rights Reserved. BEL24-D-322041 | Superlite | Revised 01/2025