SILVERLAKE

STONE FINISH | 20MM



Soft veining effects intertwine with neutral shades to offer natural patterns like those found in marble and stones. These traits provide a luxurious look with maximum versatility.













ORSI SK 06 ST



MODERATE VARIATION





HIGH VARIATION

L

LOW SOLAR HEAT

PALLET INFORMATION

| SILVERLAKE | | SQFT/ | SQFT/ | BOXES/ | PCS/ | WEIGHT/ | WEIGHT/ |
|------------|---|--------|-------|--------|------|---------|---------|
| | | PALLET | BOX | PALLET | BOX | BOX | PALLET |
| 24 X 48 | 23.54 x 47.17 x ³ / ₄ | 271.25 | 7.75 | 35 | 1 | 74 | 2621 |

Downloadable professional resources available at **Belgard.com/Resources**

QUALITY FOR LIFE

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty**

FEATURES & BENEFITS

- A range of balanced, neutral colours with soft veining effects
- Incredibly high breakage loads, up to 3,000 pounds
- · Modular for faster installation,
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials.
- Structured top textures create non-slip surfaces.
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F).
 - * It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

SHAPES & SIZES

24 X 48



23.54 x 47.17 x 3/4

View the product page on **Belgard.com** for more information

