

AQUALINE™

PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY
IN A CONTEMPORARY PERMEABLE PAVER



BELGARD
PAVES THE WAY™





AQUALINE™

PERMEABLE PAVER

LOW MAINTENANCE AND PROVEN DURABILITY IN A CONTEMPORARY PERMEABLE PAVER

☑ FEATURES & BENEFITS

- Interlocking spacer bars for increased structural performance
- Smooth surface with a micro-chamfer to minimize vibration and enhance wheelchair comfort
- Can be utilized to construct an ADA-compliant pavement
- True installed dimensions for design optimization
- Optimal joint openings for infiltration and maintenance
- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Chamfer Width: 3 mm
- Spacer Bar Width: 10 mm
- Surface Infiltration Rate: > 500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 10%
- Can be installed mechanically

🔹 AVAILABLE COLORS



FOUNDRY






MIDNIGHT




Also available in Durafusion

🧱 SHAPES & SIZES

3-PIECE AQUALINE

-  4½ x 4½ x 3⅞
-  4½ x 9 x 3⅞
-  9 x 9 x 3⅞

4½ X 9 AQUALINE

-  4½ x 9 x 3⅞