TRAVERTINI

TRAVERTINE FINISH | 20MM



Resembling the natural texture of travertine, these large-format slabs create upscale and timeless spaces with multiple aesthetic options, including linear vein or softer cross-cut looks.







Only available in 24x48





Only available in 24x48













SLIGHT ARIATION

LOW SOLAR HEAT ABSORPTION

PALLET INFORMATION

TRAVERTINI		SQFT/ PALLET	SQFT/ BOX	BOXES/ PALLET	PCS/ BOX	WEIGHT/ BOX	WEIGHT/ PALLET
24 X 24	23.54 x 23.54 x ³ / ₄	232.5	7.75	30	2	76	2280
24 X 48	23.54 x 47.17 x ³ / ₄	271.25	7.75	35	1	74	2664

Downloadable professional resources available at **Belgard.com/Resources**

QUALITY FOR LIFE


Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty**

FEATURES & BENEFITS

- Can be installed on a traditional sand or gravel base or on a pedestal system for rooftop applications
- · Timeless beauty of travertine
- Aesthetic options include a linear Vein Cut appearance and a softer Cross Cut appearance
- · Large format slabs
- · Two modular shapes offer design flexibility
- Incredibly high breakage loads, up to 3,000 pounds
- · Modular for faster installation
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials
- Structured top textures create non-slip surfaces
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F)

* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

SHAPES & SIZES



View the product page on **Belgard.com** for more information

