TRAVERTINI

TRAVERTINE FINISH | 20MM



Resembling the natural texture of travertine, the smooth finish offers two aesthetic options of either the look of linear veins or softer cross cuts.









v2 MISTY VEIN* EY 11 NAT



v2 LIGHT CROSS** EY 13 NAT



MISTY CROSS**



DARK VEIN* EY 08 NAT



v2 PEARLY CROSS**
EY 12 NAT







PALLET INFORMATION

TRAVERTINI		SQFT/ PALLET	SQFT/ BOX	BOXES/ PALLET	PCS/ BOX	WEIGHT/ BOX	WEIGHT/ Pallet
32 X 32	31.42 x 31.42 x ³ / ₄	289.33	6.88	42	1	65.48	2751
24 X 48	23.54 x 47.17 x ³ / ₄	271.25	7.75	35	1	74	2621

Downloadable professional resources available at Belgard.com/Resources

QUALITY FOR LIFE


Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty**

FEATURES & BENEFITS

- · Timeless beauty of travertine
- · Aesthetic options include a linear Vein Cut appearance and a softer Cross Cut appearance
- Large format slabs
- · A variety of modular shapes offer ultimate design flexibility
- · Incredibly high breakage loads, up to 3,000 pounds
- · Modular for faster installation
- · Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types
- · Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials
- Structured top textures create non-slip surfaces
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to $+60^{\circ}$ C (-60° F to $+140^{\circ}$ F)

* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

SHAPES & SIZES



View the product page on Belgard.com for more information

