

PORCELAIN COLLECTION

TRAVERTINI

TRAVERTINE FINISH | 20MM



Resembling the natural texture of travertine, the smooth finish offers two aesthetic options of either the look of linear veins or softer cross cuts.



v2  **LIGHT VEIN**
EY 07 NAT
Only available in 24 x 48



v2  **DARK VEIN**
EY 08 NAT
Only available in 24 x 48



v2  **MISTY VEIN**
EY 11 NAT
Only available in 24x48



v2  **PEARLY CROSS**
EY 12 NAT
Only available in 32 x 32



v2  **LIGHT CROSS**
EY 13 NAT
Only available in 32 x 32



v2  **MISTY CROSS**
EY 14 NAT
Only available in 24x48

Due to the natural materials in our products, colors may vary from those shown on the cut sheet. We recommend viewing actual product samples to ensure the perfect color and finish for each project.



SLIGHT
VARIATION



LOW SOLAR HEAT
ABSORPTION

QUALITY FOR LIFE

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at [Beldgard.com/Warranty](https://Belgard.com/Warranty)

FEATURES & BENEFITS

- Timeless beauty of travertine
- Aesthetic options include a linear Vein Cut appearance and a softer Cross Cut appearance
- Large format slabs
- A variety of modular shapes offer ultimate design flexibility
- Incredibly high breakage loads, up to 3,000 pounds
- Modular for faster installation
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials.
- Structured top textures create non-slip surfaces.
- Freeze thaw resistant—100% frost free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F).

** It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.*

SHAPES & SIZES

32 X 32



31.42 x 31.42 x 3/4

24 X 48



23.54 x 47.17 x 3/4

PALLET INFORMATION

	TRAVERTINI	SQFT/ PALLET	SQFT/ BOX	BOXES/ PALLET	PCS/ BOX	WEIGHT/ BOX	WEIGHT/ PALLET
32 X 32	31.42 x 31.42 x 3/4	289.33	6.88	42	1	65.48	2751
24 X 48	23.54 x 47.17 x 3/4	271.25	7.75	35	1	74	2621

Downloadable professional resources available at
Beldgard.com/Resources

View the product page
on Beldgard.com for
more information



LEARN MORE

BELGARD® | PAVES
THE WAY™

AN OLDCASTLE® APG OUTDOOR BRAND

STOCKTON
4202 Gibraltar Court
Stockton, CA 95206
Ph: 209-983-1609

SAN MARTIN
13775 Llagas Ave
San Martin, CA 95046
Ph: 408-686-9627

TRACY
426 E Grant Line Rd
Tracy, CA 95376
Ph: 209-833-7366

GILROY
5787 Obata Way
Gilroy, CA 95020
Ph: 408-984-8800

© 2025 Oldcastle® APG, Inc. All Rights Reserved. BEL24-D-322433 | Pacific Stockton | Revised 01/2025