
# DIAMOND PRO PS SMOOTH



RETAINING

A refined appearance with clean lines and the strength of Diamond Pro Retaining Wall Systems, this wall provides a modern touch and is efficiently installed with a pin system.



Swatch represents product color only, not surface texture.







## PALLET INFORMATION

	DIAMOND PRO° PS SMOOTH	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ Pallet	WEIGHT/ Pallet
SM00TH FACE	8 x 18 x 12	36	-	-	36	2550
UNIVERSAL	4 x 17¼ / 12 x 10	78.75	-	-	80	3100

Downloadable professional resources available at **Belgard.com/Resources** 

#### QUALITY FOR LIFE

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty** 

# FEATURES & BENEFITS

- Contemporary smooth face and clean lines
- · Pin system installation method
- Large cores for ease in handling
- Ease of installation with oversized pin aligning cores
- · Pin cores allow for multiple batter options
- Builds walls in excess of 50 feet when combined with geosynthetic reinforcement
- One square foot of wall face per block
- Gravity walls can be built up to 4 feet high\*, including the buried course, with
  7.1 degree batter
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet
- Setback/System Batter: Near Vertical and 1"/7.1°; additional system batter can be created by alternating pin placement on each course of wall

\*Gravity wall heights are based on project specific conditions and may be lower than this value.

## SHAPES & SIZES

SMOOTH FACE



8 x 18 x 12

UNIVERSAL CAP



4 x 17¼ / 12 x 10

PS: Pin System. Pins Included

View the product page on **Belgard.com** for more information

