

COMMERCIAL

PRODUCT OFFERING

MIDWEST

MICHIGAN, MINNESOTA, NEBRASKA, NORTH DAKOTA,
IOWA, ILLINOIS, INDIANA, KENTUCKY, OHIO, SOUTH
DAKOTA, WISCONSIN, WESTERN PENNSYLVANIA,
KANSAS, MISSOURI, NORTHEAST OKLAHOMA
& ARKANSAS



BELGARD
COMMERCIAL

PAVER APPLICATIONS



Pedestrian

Designated for areas that are primarily for pedestrian applications, including commercial plazas that may require occasional access for emergency or maintenance vehicles, as well as residential driveways.



Light Vehicles

Designated for commercial vehicular areas, access ways, and parking lots where only cars and light trucks are anticipated. Heavy vehicles should have limited access and use.



Occasional Heavy Vehicles

Designated for vehicular areas, parking lots, and roadways where limited heavy vehicles are anticipated daily, such as large delivery trucks or garbage trucks.



Frequent Heavy Vehicles

Designated for vehicular areas, parking lots, and roadways where heavy vehicles are a regular component of the daily traffic volume.

Paver application icons are general recommendations. Site conditions and pavement cross section must be considered. Paver application icons are based on placement over unbound aggregates for setting beds, base and subbase.

PAVER COLORS & FINISHES

Standard Colors



GRAPHITE



FOUNDRY



LINEN*



COTSWOLD MIST

** Light colored paver has an SRI value of ≥ 29 and/or an SR value of ≥ 0.33*

Regional Colors

In addition to our standard color offering, Belgard Commercial products come in a number of local colors. Check with your local Belgard Sales Representative for more information.


Finishes

Manufacturing processes generate various finishes that are distinctive and can create the exact look you desire for your project. All processes are not available in all locations. Check with your local Belgard Sales Representative for more information.



Standard (smooth)

Unit surfaces and micro-chamfers are carefully molded using a high-quality precision machined steel shoe assembly which creates units with an extremely smooth surface and precision detailed chamfer.



Ground Face

The top of the paving units are ground smooth which exposes the aggregate colors and pigmented background.



Shot Blast

Exposes the surface of the paving unit to reveal the natural beauty of the aggregates and pigmentation. Shot Blast cannot be combined with DuraFusion.



Antiqued

Units are molded to form specific surface and side textures that are processed through tumbling equipment, imparting a distressed or aged appearance.

DuraFusion™

DuraFusion fuses a top layer of rich pigments with Belgard's core color process. The result is a paver with a richness and purity of color that's sleek and vibrant.



















DuraFusion™ + ColorTech™

DuraFusion™ + ColorTech™ multiplies the enhancement of DuraFusion™ with the protection of ColorTech™ to offer the highest quality concrete paver available today. The result is a smooth, gentle finish and vibrant color blend with unmatched protection against fading, stains and scratches.

ColorTech™

Belgard's exclusive premium surface level color-enhancing protectant. ColorTech enhances the original color depth of Belgard pavers and extends color fastness and durability over time. ColorTech is not a sealer, and does not create a glossy or wet look. It enhances the original color of the paver without losing the surface texture of real stone.

DIMENSIONS™ SERIES VEHICULAR & ARCHITECTURAL PAVERS

| UNITS | THICKNESS | SIZE | APPLICATIONS | | | | ADA* | FINISHES | | | | | CHAMFER WIDTH | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) |
|---|----------------------------|-----------|---|---|---|---|------|---|----------|-------------|------------|------------|---------------|--|--|--|
| | | |  |  |  |  | |  | Standard | Ground Face | Shot Blast | DuraFusion | | | | |
|  3" x 12" | 60 mm 80 mm | 3" x 12" | 60 mm | 80 mm | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 110 (60 mm) 88 (80 mm) | 440 (60 mm) 352 (80 mm) | 3,102 (60 mm) 3,300 (80 mm) |
|  6" x 6" | 60 mm 80 mm 101.6 mm | 6" x 6" | 60 mm 80 mm 101.6 mm | 80 mm 101.6 mm | 101.6 mm | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 (60 mm) 96 (80 mm) 72 (101 mm) | 480 (60 mm) 384 (80 mm) 288 (101 mm) | 3,173 (60 mm) 3,590 (80 mm) 3,370 (101 mm) |
|  6" x 9" | 60 mm 80 mm | 6" x 9" | 60 mm | 80 mm | 80 mm | 80 mm | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 112.5 (60 mm) 90 (80 mm) | 300 (60 mm) 240 (80 mm) | 3,173 (60 mm) 3,366 (80 mm) |
|  6" x 12" | 60 mm 80 mm 101.6 mm | 6" x 12" | 60 mm 80 mm 101.6 mm | 80 mm 101.6 mm | 101.6 mm | 101.6 mm | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 (60 mm) 96 (80 mm) 72 (101 mm) | 240 (60 mm) 192 (80 mm) 144 (101 mm) | 3,384 (60 mm) 3,717 (80 mm) 3,370 (101 mm) |
|  12" x 12" | 60 mm 80 mm 101.6 mm | 12" x 12" | 60 mm 80 mm 101.6 mm | 80 mm 101.6 mm | 101.6 mm | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 (60 mm) 96 (80 mm) 72 (101 mm) | 120 (60 mm) 96 (80 mm) 72 (101 mm) | 3,384 (60 mm) 3,590 (80 mm) 3,370 (101 mm) |
|  12" x 12" ADA | 60 mm | 12" x 12" | 60 mm | | | | ✓ | ✓ | | | | | 3 mm | 120 | 120 | 3,384 |
|  12" x 18" | 60 mm | 12" x 18" | 60 mm | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 | 80 | 3,384 |
|  12" x 24" | 60 mm | 12" x 24" | 60 mm | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 | 60 | 3,384 |
|  18" x 18" | 60 mm | 18" x 18" | 60 mm | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 90 | 40 | 2,511 |
|  18" x 24" | 60 mm | 18" x 24" | 60 mm | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 3 mm | 120 | 40 | 3,348 |
|  24" x 24" | 60 mm | 24" x 24" | 60 mm | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | 3 mm | 80 | 20 | 2,256 |
|  24" x 30" | 60 mm | 24" x 30" | 60 mm | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | 3 mm | 100 | 20 | 2,820 |
|  24" x 36" | 60 mm | 24" x 36" | 60 mm | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | 3 mm | 120 | 20 | 3,300 |








Note: The Dimensions Series is all made to order. Lead times will apply. Check with your local Belgard representative for applicable lead times.

Interlocking pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard representative in your area before specifying products for vehicular applications.













* May be suitable for ADA applications. Always evaluate site-specific uses to ensure surface suitability. Product installation and surface maintenance influence compliance with ADA Standards for Accessible Design Section 302 Floors or Ground Surfaces. Tumbling or antiquing pavers can also create surface or edges that may make the product unsuitable for ADA applications.

Secondary processes and finishes including, but not limited to, face-grinding, may impact dimensional tolerances from base dimensions.

MODULINE PLANKS

| UNITS | THICKNESS | SIZE | APPLICATIONS | | | | ADA* | MECHANICAL INSTALL | FINISHES | | | | | | CHAMFER WIDTH | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) | |
|---|-----------|----------|---|---|---|---|------|--------------------|---|---|----------|-------------|------------|----------|---------------|--------------------|-----------------|---------------------|------------|
| | | |  |  |  |  | | |  |  | Standard | Ground Face | Shot Blast | Antiqued | | | | | DuraFusion |
|  4" x 18" | 80 mm | 4" x 18" | 80 mm | | | | | ✓ | | ✓ | ✓ | ✓ | | ✓ | ✓ | 3 mm | 72 | 144 | 2,706 |

VEHICULAR & ARCHITECTURAL PAVERS

| UNITS | THICKNESS | SIZE | APPLICATIONS | | | | ADA* | MECH. INSTALL | FINISHES | | | | | | | CHAMFER WIDTH | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) | |
|---|----------------------------|--------------------------------|---|--|---|---|------|---------------|---|---|----------|-------------|------------|----------|------------|---------------|--------------------|---|--|--|
| | | |  |  |  |  | | |  |  | Standard | Ground Face | Shot Blast | Antiqued | DuraFusion | | | | | ColorTech |
|  Brooklyn | 60 mm | 3" x 9" | 60mm | | | | | ✓ | | | | | | | | ✓ | N/A | 103.13 | 550 | 2,805 |
|  Charlestone™ | 60 mm | 6" x 6" 6" x 9" 6" x 12" | 60 mm | | | | | | | | | | | | ✓ | | Rolled Edge | 103.88 | 270 | 2,997 |
|  Dimensions™ 6 | 60 mm | 3" x 6" 6" x 6" 6" x 9" | 60 mm | | | | | ✓ | | ✓ | | | | ✓ | | | 3 mm | 120 | 480 | 3,516 |
|  Holland Stone | 60 mm 80 mm | 4" x 8" | 60 mm | 80 mm | 80 mm | 80 mm | | ✓ | 80 mm (Herringbone pattern) | ✓ | | | ✓ | ✓ | ✓ | | 7 mm | 105 82 | 486 378 | 3,112 3,348 |
|  Origins™ 6 | 60 mm | 3" x 6" 6" x 6" 6" x 9" | 60 mm | | | | | ✓ | | | | | | ✓ | | | 3 mm | 120 | 480 | 3,516 |
|  6" Bishop Hat | 60 mm 80 mm 101.6 mm | 6" Bishop Hat | 60 mm 80 mm 101.6 mm | 80 mm 101.6 mm | 80 mm 101.6 mm | 80 mm 101.6 mm | | ✓ | | ✓ | ✓ | ✓ | | ✓ | ✓ | | 3 mm | 84.5 (60 mm) 67.6 (80 mm) 50.7 (101 mm) | 280 (60 mm) 224 (80 mm) 168 (101 mm) | 2,383 (60 mm) 2,528 (80 mm) 2,373 (101 mm) |

Note: The Moduline Series is all made to order. Lead times will apply. Check with your local Belgard representative for applicable lead times.

Interlocking pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard representative in your area before specifying products for vehicular applications.








* May be suitable for ADA applications. Always evaluate site-specific uses to ensure surface suitability. Product installation and surface maintenance influence compliance with ADA Standards for Accessible Design Section 302 Floors or Ground Surfaces. Tumbling or antiquing pavers can also create surface or edges that may make the product unsuitable for ADA applications.

Secondary processes and finishes including, but not limited to, face-grinding, may impact dimensional tolerances from base dimensions.

PERMEABLE PAVERS

| UNITS | THICKNESS | SIZE | APPLICATIONS | | | | ADA* | MECHANICAL INSTALL | FINISHES | | | | | | MANUF. JOINT WIDTH | % SURFACE OPENING | CHAMFER WIDTH | SQ. FT. PER PALLET | PALLET WEIGHT | |
|--|-----------|--|---|--|---|---|------|--------------------|---|---|----------|-------------|------------|----------|--------------------|-------------------|---------------|--------------------|--|------------|
| | | |  |  |  |  | | |  |  | Standard | Ground Face | Shot Blast | Antiqued | | | | | | DuraFusion |
| AQUALINE™ SERIES (all sizes made to order) | | | | | | | | | | | | | | | | | | | | |
|  3" x 12" | 80 mm | 3" x 12" | ✓ | ✓ | | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | 7 mm | 10% | 3 mm | 88 | 3,291 |
|  4½" x 9" | 80 mm | 4½" x 9" | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | 10 mm | 10% | 3 mm | 90 | 3,423 |
|  4½" x 9" Herringbone | 80 mm | 4½" x 9" | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | ✓ | ✓ | 10 mm | 10% | 3 mm | 90 (36 full units/ layer; 8 half units/layer) | 3,423 |
|  6" x 6" | 80 mm | 6" x 6" | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | 7 mm | 7% | 3 mm | 96 | 3,590 |
|  6" x 12" | 80 mm | 6" x 12" | ✓ | ✓ | | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | 7 mm | 5% | 3 mm | 96 | 3,590 |
|  12" x 12" | 80 mm | 12" x 12" | ✓ | ✓ | | | ✓ | | ✓ | ✓ | ✓ | | | ✓ | ✓ | 7 mm | 3% | 3 mm | 96 | 3,590 |
|  9" x 9" L-Stone | 80 mm | 9" x 9" | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | ✓ | ✓ | 10 mm | 10% | 3 mm | 90 | 3,375 |
| ADDITIONAL PRODUCT LINES | | | | | | | | | | | | | | | | | | | | |
|  Aqua Roc™ | 80 mm | 4½" x 9" | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | | | | | | ✓ | 8 mm | 9% | 3 mm | Check with your local Belgard Sales Rep. | |
|  Aqua Roc™ II | 80 mm | 4" x 8" | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | ✓ | 8 mm | 9% | 3 mm | 92 | 3,036 |
|  Eco Dublin® | 80 mm | 6 ¹⁵ / ₁₆ " x 3 ³ / ₁₆ " 6 ¹⁵ / ₁₆ " x 6 ¹⁵ / ₁₆ " 6 ¹⁵ / ₁₆ " x 10 ⁵ / ₁₆ " | ✓ | ✓ | | | ✓ | ✓ | ✓ | | | | | | ✓ | 12 mm | 7% | N/A | Check with your local Belgard Sales Rep. | |
|  Holland Permeable | 80 mm | 5" x 10" | ✓ | ✓ | | | ✓ | ✓ | ✓ | | | | | ✓ | 10 mm | 7% | 2 mm | | | |










CONCRETE GRID PAVEMENTS

| UNITS | THICKNESS | SIZE | APPLICATIONS | | | | ADA | MECHANICAL INSTALL | FINISHES | | | | % SURFACE OPENING | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) | |
|--|-----------|-------------|---|--|---|---|-----|--------------------|---|---|----------|-------------|-------------------|--------------------|-----------------|---------------------|------------|
| | | |  |  |  |  | | |  |  | Standard | Ground Face | | | | | Shot Blast |
|  Turfstone™ | 80 mm | 15¾" x 23⅝" | 80 mm | | | | | | ✓ | | | | | 40% | 103.2 | 40 | 2,377 |

* May be Suitable for ADA applications. Always evaluate site-specific uses to ensure surface suitability. Product installation and surface maintenance influence compliance with ADA Standards for Accessible Design Section 302 Floors or Ground Surfaces. Tumbling or antiquing pavers can also create surface or edges that may make the product unsuitable for ADA applications.

Secondary processes and finishes including, but not limited to, face-grinding, may impact dimensional tolerances from base dimensions.

PORCELAIN PAVERS

| UNITS | APPEARANCE | THICKNESS | SIZE | COLOR OPTIONS | ADA | PEDESTAL APPLICATION | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) |
|--|---------------|-----------|-----------|--|---|----------------------|--------------------|-----------------|---------------------|
| | | | | |  | | | | |
|  Glocal | Concrete | ¾" | 24" x 24" | Clear, Ideal, Type, Classic | ✓ | ✓ | 232.5 | 60 | 2,160 |
|  Noon - 8 x 48 | Wood | ¾" | 8" x 48" | Daylight, Ember, Honey | ✓ | ✓ | 151.8 | 60 | 1,415 |
|  Noon - 12 x 48 | Wood | ¾" | 12" x 48" | Daylight, Ember, Honey | ✓ | ✓ | 279 | 72 | 2,664 |
|  Quarziti 2.0 | Stone | ¾" | 24" x 24" | Glacier, Mountains, Waterfall, River, Mantle | ✓ | ✓ | 232.5 | 60 | 2160 |
|  Quarziti 2.0 | Stone | ¾" | 24" x 48" | Glacier, Mountains, Waterfall, River, Mantle | ✓ | ✓ | 271.25 | 35 | 2,621 |
|  Unico | Various | ¾" | 13" x 24" | Glacier, Mountains, Waterfall, River, Mantle, Daylight, Ember, Honey | ✓ | ✓ | 254.82 | 120 | 2,080 |
|  Porcelain Veneer | Stone or Wood | ¾" | 4" x 17½" | Glacier, Mountains, Waterfall, River, Mantle, Daylight, Ember, Honey | | | 390.7 | 770 | 1,900 |
|  Verona | Stone | ¾" | 24" x 24" | Blue Stone, Platinum, Taos, Yukon | ✓ | ✓ | 232.5 | 60 | 2,160 |

ROOFTOP PAVERS & ACCESSORIES

| UNITS | THICKNESS | SIZE | MATERIAL | FINISHES | | | PEDESTAL APPLICATION | PCS. PER PALLET | WEIGHT PER SQ. FT. (LBS) |
|---|-----------|--------------------------------------|---------------------------------------|----------|--------|------------|----------------------|--|--------------------------|
| | | | | Diamond | Smooth | Shot Blast | | | |
| ROOFTOP PAVERS | | | | | | | | | |
| Ballast Pavers | 1½" | 16" x 8½" | Concrete | | | | ✓ | - | 13.75 |
| Classic Plaza Slab | 1⅞" | 24" x 24" | Concrete | ✓ | ✓ | ✓ | ✓ | Varies 22-25 <i>Contact Belgard Representative for info</i> | 23 |
| Porcelain Plaza Pavers | ¾" | See page 14 | Porcelain | | ✓ | | ✓ | - | - |
| Wood Plaza Paver | 1½" | 24" x 24" 24" x 48" | Ipe Wood | | ✓ | | ✓ | - | 5.56 |
| ACCESSORIES | | | | | | | | | |
| Cubes & Cube Tops <i>(Made to order, custom sizes available)</i> | - | 24" x 24" x 16½" 48" x 24" x 16½" | Ipe Wood or Powder Coated Aluminum | | ✓ | | ✓ | - | - |
| Pedestals - Fixed Height | - | ¼", ½", ¾" height | - | | | | ✓ | - | - |
| Pedestals - Adjustable | - | 1¼" - 36" height* | - | | | | ✓ | - | - |

Classic Plaza Slab Colors



Chamois



Charcoal



Ginger



SRI White**



Cinnamon



Limestone



Natural



Red



* Higher heights require extension couplers. Additionally, heights over 24" require bracing.

**SRI Color - Solar Reflective Index in excess of 80

SEGMENTAL RETAINING AND FREESTANDING WALLS (SRW & FSW)

| UNITS | UNIT SIZE | | | CONNECTION TYPE | | ACCESSORIES* (SOLD SEPARATELY) | | TEXTURE | | FACE STYLES | | | | BATTER/ SETBACK | SQ. FT. PER PALLET | PCS. PER PALLET | PALLET WEIGHT (LBS) |
|---|----------------------------------|--|---------------------------------|-----------------|---|-----------------------------------|----------|----------|-------|-------------|---------|------------------|-----------|---|--|--------------------|---------------------------|
| | Height | Width | Depth | Block | Other | Column/ Corner Unit | Cap Unit | Sculpted | Split | Straight | Beveled | Virtual Joint | Stone Cut | | | | |
|  Ashlar Tandem™ | 7" | 13 ³ / ₁₆ ", 15 ¹ / ₁₆ ", 18 ¹ / ₁₆ " | 2 ⁵ / ₈ " | | Polypropylene Connectors or Modular Block | | | ✓ | | | | | | 0 / 4° | 70.1 | 90 | 2082 |
|  Lamina Tandem™ | 7" | 15 ¹ / ₁₆ ", 18 ⁷ / ₁₆ ", 21 ¹ / ₁₆ " | 2 ⁵ / ₈ " | | Polypropylene Connectors or Modular Block | | | ✓ | | | | | | 0 / 4° | 56.08 | 72 | 1666 |
|  Melville Tandem™ | 7" | 13 ³ / ₁₆ ", 15 ¹ / ₁₆ ", 18 ¹ / ₁₆ " | 2 ⁵ / ₈ " | | Polypropylene Connectors or Modular Block | | | | | ✓ | | | | 0 / 4° | 70.1 | 90 | 2082 |
|  Tandem Modular Block | 7 ¹ / ₁₆ " | 7 ⁷ / ₈ " | 7 ⁷ / ₈ " | | | | | | | | | | | N/A | 49.29 | 128 | 2816 |
|  Belair Wall® 2.0 Freestanding Wall | 6" | 6", 10", 16" | 5" | | | ✓ | ✓ | ✓ | | | | | | Vertical | 60 | 120 | 3080 |
|  Belair Wall® 2.0 Retaining Wall | 6" | 6", 10", 16" | 8" | Rear Lip | | ✓ | ✓ | ✓ | | | | | | 9°; 1" Per Course | 30 | 60 | 2406 |
|  Diamond Pro® | 8" | 18" | 12" | Rear Lip | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | 7.1°; 1" Per Course | Check with your local Belgard Sales Rep. | | |
|  Diamond Pro® PS | 8" | 18" | 12" | | Fiberglass Pin | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | Front Pinholes: 1.7°; .23" Per Course Back Pinholes: 7.1°; 1" Per Course | Check with your local Belgard Sales Rep. | | |
|  Highland Stone® SRW Small & Medum | 6" | 12", 6" | 12" | Rear Lip | | ✓ | ✓ | | ✓ | ✓ | | | | 10.6°; 1.125" Per Course | 24 | 64 | 2912 |
|  Highland Stone® SRW Large | 6" | 18" | 12" | Rear Lip | | ✓ | ✓ | | ✓ | ✓ | | | | 10.6°; 1.125" Per Course | 24 | 32 | 2592 |
|  Highland Stone® FSW Small & Medium | 6" | 12", 6" | 9" | | | ✓ | ✓ | | ✓ | ✓ | | | | Vertical | 26.8 | 80 | 3280 |
|  Highland Stone® FSW Large | 6" | 18" | 9" | | | ✓ | ✓ | | ✓ | ✓ | | | | Vertical | 28.4 | 40 | 3480 |
|  Sterling® | 6" | 17 ³ / ₄ " | 12" | | Fiberglass Pins | | ✓ | | ✓ | ✓ | | | | 10.6° | 33.3 | 45 | 3983 |



AQUALINE 9" L-STONE



AQUALINE 9" L-STONE

PROFESSIONAL SUPPORT



ENVIRONMENTAL SOLUTIONS

Belgard consultants can work with your team to develop the best PICP system design or retaining wall configuration to control runoff volume and discharge rates, improve the quality of local groundwater, reduce or prevent downstream impacts, and minimize the land consumed for stormwater management.



CAD FILES

For your convenience, Belgard offers a constantly expanding library of easy-to-download CAD files of our products and patterns.



CONTINUING EDUCATION

Belgard offers a variety of ongoing educational programs for our industry partners, including Lunch & Learns, online CEU courses, and our Belgard University training program.



SITE PLANNING

The experts at Belgard can help you optimize your site in a number of ways—whether you're looking for creative ways to define public spaces, manage or harvest stormwater, or increase the usable space for development.



ENGINEERING SERVICES

Our team of design consultants can help address both aesthetic and engineering design concerns, material quantity estimates and permit ready plans.

MIDWEST LOCATIONS



One Hunt Court
Mundelein, IL 60060
Ph: 877-222-1557
FX: 847-816-9062
Chicagoland: 847-949-3600

901 E. Troy Avenue
Indianapolis, IN 46203
Ph: 800-424-0190

5190 Oster Road
Sheffield Village, OH 44054
Ph: 440-949-1167

480 South 16th Street
West Des Moines, IA 50265
Ph: 515-224-0200
Ph: 866-761-4552

5909 Baker Road, Suite 550
Minnetonka, MN 55345
Ph: 800-440-8657

13450 Johnson Memorial Drive
Shakopee MN 55379
Ph: 952-351-9630

3400 Bungalow Rd
Morris, IL 60450
Ph: 847-949-3600

4201 Powell Drive
Bonner Springs, KS 66012
Ph: 913-667-1792
Ph: 800-289-2244



[BELGARDCOMMERCIAL.COM](https://www.belgardcommercial.com)